



WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk




EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322



13.06.2017

АНАЛОГНИ КАМЕРИ

1.		Waterproof IR-Bullet Camera DAHUA CA-FW181JP-B-IR Image Sensor: 1/3" HDIS ; Effective Pixels: 960(H)×480(V) ; Horizontal Resolution: 720TVL ; Electronic Shutter: 1/50s~1/100,000s ; Min. Illumination: 0.02Lux@F1.2(AGC ON), 0Lux IR on ; S/N Ratio: More than 65dB(AGC Off) ; Video Output: 1Vp-p Composite Output (75Ω/BNC) ; Max. IR LEDs Length: 50m, Smart IR ; Day/Night: Auto(ICR) / Color / B/W ; Backlight Compensation: BLC ; White Balance: Auto ; Gain Control: Auto ; Focal length: 6mm fixed lens ; Angle of View: H: 46.5° ; Power Supply: DC12V±10% ; Power Consumption: Max 6W ; Working Environment: -40°C ~+60°C / 20%~80%RH ; Ingress Protection: IP66 ; With bracket	43-€ 36 €
2.		IR Bullet Camera DAHUA DH-CA-FW480DP Image Sensor: 1/3" EXview HAD CCD II ; Effective Pixels: 976(H)×582(V), 570K pixels ; Horizontal Resolution: 700TVL ; Electronic Shutter: 1/50s~1/100,000s ; Min. Illumination: 0.001Lux@F1.2(AGC ON), 0Lux IR on ; S/N Ratio: >65dB ; Video Output: 1Vp-p Composite Output (75Ω/BNC) ; Max. IR LEDs Length: 50m, Smart IR ; Day/Night: Auto(Electronic) / Color / B/W ; Backlight Compensation: BLC ; White Balance: Auto ; Gain Control: Auto ; Focal Length: 3.6mm ; Angle of View: H: 70° ; Power Supply: DC12V±10% ; Power Consumption: Max 5.5W ; Working Environment: -40°C~+60°C / 20%~80%RH ; Ingress Protection: IP66 ; Without bracket	42 €
3.		Waterproof IR camera DAHUA DH-CA-FW171 Image Sensor: 1/3" HDIS ; Horizontal Resolution: Color: 600TVL ; Electronic Shutter: 1/50s ~ 1/100,000s ; Min. Illumination: 0.1Lux@F1.2(0Lux IR LED on) ; S/N Ratio: >60dB(AGC Off) ; Video Output: 1Vp-p Composite Output (75Ω/BNC) ; Max. IR LEDs Length: 30m, Smart IR ; Day/Night: Auto(ICR) / Color / B/W ; Backlight Compensation: BLC ; White Balance: Auto ; Gain Control: Auto ; Focal length: 2.8~12mm ; Power Supply: DC12V±10% (-A model: DC12V/AC24V dual power supply) ; Power Consumption: Max 4.5W ; Working Environment: -40°C~+60°C / 20%~80%RH ; Ingress Protection: IP66 ; With bracket	55 €
HDCVI КАМЕРИ			
4.		1MP HDCVI Mini Dome Camera DAHUA DH-HAC-HDW1000R-S3 Image Sensor: 1Megapixel CMOS ; Effective Pixels: 1280(H)×720(V) ; Electronic Shutter: 1/50s~1/100,000s ; Video Frame Rate: 25fps@720P ; Synchronization: Internal ; Min. Illumination: 0.01Lux@F1.2(AGC ON), 0Lux IR on ; Video Output: 1-channel BNC HDCVI high definition video output ; Max. IR LEDs Length: 15m, Smart IR ; Day/Night: Auto(ICR) / Color / B/W ; Noise Reduction: 2D ; Focal Length: 2.8mm fixed lens ; Angle of View: H: 83.4° ; Power Supply: DC12V±20% ; Power Consumption: Max 2.5W ; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation) ; Transmission Distance: Over 800m via 75-3 coaxial cable ; Material: Plastic.	14-€ 9.9 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

5.		2MP HDCVI Camera DAHUA DH-HAC-HDW1200RP-S3 Image Sensor: 1/2.7" 2Megapixel CMOS; Effective Pixels: 1920(H)×1080(V); High speed, long distance real-time transmission; Electronic Shutter: 1/25~1/100000s; Video Frame Rate:25/50fps@720P; 25fps@1080P; Min. Illumination: 0.02Lux/F2.0, 0Lux IR on; Video Output:1-channel BNC high definition video output/ CVBS standard definition video output (Can switch); Focal Length: 3.6mm ; Angle of View: H: 89.9°; Max. IR LEDs Length: 20m, Smart IR ; Day/Night: Auto(ICR)/Color/B/W; Power Supply: DC12V±25% ; Power Consumption: Max 2.8W ; Working Environment: -40°C~+55°C / Less than 95%RH (no condensation); Transmission Distance: 500m via 75-3 coaxial cable ; Material: Plastic	23-€ 16.9 €
6.		2MP Waterproof HDCVI Camera DAHUA DH-HAC-HDW1200MP Image Sensor: 1/2.7" 2Megapixel CMOS; Effective Pixels: 1930(H)×1088(V); High speed, long distance real-time transmission; Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@1080P; Min. Illumination: 0.01Lux@F1.2(AGC ON), 0Lux IR on; Video Output: 1-channel BNC HDCVI high definition video output; Focal Length: 3.6mm; Angle of View: H: 80.6°; Max. IR LEDs Length: 20m, Smart IR ; Day/Night(ICR), AWB, AGC, BLC, 2D-DNR ; Power Supply: DC12V±20% ; Power Consumption: Max 2.5W ; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation) ; Transmission Distance: 300m via 75-3 coaxial cable ; Ingress Protection: IP66 ; Material: Metal	33-€ 29 €
7.		2MP HDCVI Dome Camera DAHUA DH-HAC-HDW1200EMP-A 1/2.7" 2 megapixel CMOS; Built-in microphone; 25 frames/s at a resolution of 1080p; High speed data transmission over long distances; Effective Pixels: 1930 (H) x 1088 (V); Electronic shutter: 1.3 (s) = 1/100, 000s; Day / Night (ICR), AWB, AGC, BLC, 2DNR; Focal length: 3.6mm (viewing angle 90 °); IR illumination 50m, Smart IR; Degree of protection: IP67; Power: DC12V ± 10%; Power consumption: max 4.5W; Work environment: -30°C ~ +60°C / Less than 95% (non-condensing)	34-€ 31 €
8.		2.1MP Waterproof HDCVI Dome Camera DAHUA DH-HAC-HDW2221EM-A 1/2.7" 2.1Megapixel CMOS; 25/30fps@1080P, 25/30/50/60fps@720P; Effective Pixels: 1928(H) × 1088(V); Electronic Shutter 1/3s~1/300,000s; Mini. Illumination: 0.03Lux/F2.0, 0Lux IR on; HD and SD dual-output; OSD Menu, control over coaxial cable; Built-in MIC ; WDR (120dB), Day/Night(ICR), AWB, AGC, BLC, 3DNR; 3.6mm fixed lens, Angle of View H: 90°; Max. IR LEDs length 50m, Smart IR ; Power Supply: DC12V±25%, Power Consumption: Max 5.5W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance Over 500m via 75-3 coaxial cable; Ingress Protection: IP67	41-€ 38 €
9.		2MP Vandalproof IR HDCVI Dome Camera DAHUA DH-HAC-HDBW2220RP-VF Image Sensor: 1/2.9" 2Megapixel CMOS; Effective Pixels: 1984(H)×1105(V); Video Output: 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch); Min. Illumination: 0.005Lux@F1.2(AGC ON), 0Lux IR on; Max. IR LEDs Length 30m, Smart IR; OSD Menu, control over coaxial cable; Day/Night(ICR), AWB, AGC, BLC, 3D-DNR; Focal Length: 2.7~12mm; Power Supply: DC12V±10%, Power Consumption: Max 5W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance Over 300m via 75-3 coaxial cable; Ingress Protection: IP66 & IK10	39 €
10.		2MP Waterproof HDCVI IR Dome Camera DAHUA DH-HAC-HDW1200R-VF Image Sensor: 1/2.7" 2Megapixel CMOS; Effective Pixels: 1930(H)×1088(V); Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@1080P; Synchronization: Internal; Min. Illumination: 0.01Lux@F1.2(AGC ON), 0Lux IR on; Video Output: 1-channel BNC HDCVI high definition video output; Max. IR LEDs Length: 30m, Smart IR; Day/Night: Auto(ICR) / Color / B/W; Noise Reduction: 2D. Focal length: 2.7-12mm ; Angle of View: H: 99°~37°; Mount Type: Φ14; Power Supply: DC12V±20%;Power Consumption: Max 3.8W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance: Over 500m via 75-3 coaxial cable; Ingress Protection: IP67; Material: Metal.	46-€ 45 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

11.		4MP HDCVI WDR IR Eyeball Camera DAHUA DH-HAC-HDW2401MP Image Sensor: 1/3" CMOS ; Effective Pixels: 2688(H)×1520(V), 4.1MP; Electronic Shutter Speed: 1/3s~1/300,000s; Minimum Illumination: 0.03Lux/F1.5, 0Lux IR on; S/N Ratio More than 65dB; IR Distance Up to 30m; Focal Length: 3.6mm, Angle of View H: 78° ; Resolution: 4MP (2560×1440); Frame Rate: 25fps@4MP, 25/30fps@1080P, 25/30fps@720P; Day/Night Auto (ICR) / Manual; WDR 120dB; BLC / HLC / WDR; OSD Menu Multi-language; Power Supply: 12V DC ±25%; Power Consumption: Max 7W (12V DC, IR on); HD and SD dual-output; Ingress Protection & Vandal Resistance: IP67	61€ 55 €
12.		4MP HDCVI WDR Fisheye Camera DAHUA DH-HAC-EB2401P Image Sensor: 1/3" CMOS ; Effective Pixels: 2688(H)×1520(V), 4.1MP; Minimum Illumination: 0.01Lux/F2.0 (Color), 0.001Lux/F2.0(B/W); S/N Ratio: More than 65dB; Focal Length: 1.18mm panoramic lens, Angle of View: H: 180° ; Video Output: 1-channel BNC HDCVI high definition video output & 1-channel BNC CVBS video output; Resolution: 4MP (2560×1440) ; Frame Rate: 25fps@4MP; 120dB True WDR, 3DNR; Power Supply: 12V DC ±25%; Operating Conditions: -30°C ~ +60°C / Less than 90% RH; Ingress Protection & Vandal Resistance: IK10 ; Casing: Aluminium	HOBO!!! 77 €
13.		2MP HDCVI Motion Eye Camera DAHUA DH-HAC-HUM1220AP Image Sensor: 1/2.9" CMOS ; Effective Pixels: 1920(H)×1080(V), 2MP; Minimum Illumination: 0.02Lux/F2.0 (Color), 0.002Lux/F2.0(B/W); S/N Ratio: More than 65dB; Focal Length: 2.8mm, Angle of View H: 100.5°; Resolution: 1080P (1920×1080) ; Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P; Video Output 1-channel BNC high definition video output / CVBS video output (Can switch); BLC / HLC / DWDR, Noise Reduction: 2D; Detection Range: 12mx12m, 100°, 19 zones ; Power Supply 12V DC ±25%; Power Consumption: Max 0.7W (12V DC, IR on); Casing: Plastic	40 €
14.		1MP Waterproof HDCVI IR-Bullet Camera DAHUA DH-HAC-HFW1000RP-S3 Image Sensor: 1Megapixel CMOS ; Effective Pixels: 1280(H)×720(V) ; Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@720P ; Synchronization: Internal; Mini. Illumination: 0.01Lux@F1.2 (AGC ON), 0Lux IR on; Video Output: 1-channel BNC HDCVI high definition video output. Camera Features: Max. IR LEDs Length: 15m, Smart IR ; Day/Night: Auto(ICR) / Color / B/W; Noise Reduction: 2D. Focal Length: 2.8mm fixed lens ; Angle of View: H: 83.4°; Mount Type: M12. General: Power Supply: DC12V±20%; Power Consumption: Max 3.5W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance: Over 800m via 75-3 coaxial cable ; Ingress Protection: IP67 ; Dimensions(W×D×H): 70mm×154mm; Weight: 0.2kg; Material: Plastic.	12€ 11 €
15.		1MP Waterproof HDCVI IR-Bullet Camera DAHUA DH-HAC-HFW1100D-B Image Sensor: 1/2.9" 1Megapixel CMOS ; Effective Pixels: 1280(H)×720(V) ; Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@720P; Synchronization: Internal; Min. Illumination: 0.01Lux@F1.2 (AGC ON), 0Lux IR LED on; Video Output: 1-channel BNC HDCVI high definition video output. Camera Features: Max. IR LEDs Length: 80m, Smart IR ; Day/Night: Auto(ICR) / Color / B/W; Noise Reduction: 2D. Focal length: 3.6 mm ; Angle of View: H: 88°; Mount Type: M12. General: Power Supply: DC12V±10%; Power Consumption: Max 7W; Working Environment: -30°C~+60°C/ Less than 95%RH (no condensation); Transmission Distance: Over 800m via 75-3 coaxial cable ; Ingress Protection: IP67 ; Material: Metal (front) + Plastic (body).	30€ 23 €
16.		2MP Waterproof HDCVI Bullet Camera DAHUA DH-HAC-HFW1200RP-S3 Image Sensor: 1/2.7" 2Megapixel CMOS ; Effective Pixels: 1930(H)×1088(V) ; Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@1080P ; Mini. Illumination: 0.02Lux/F2.0, 0Lux IR on; Video Output: 1-channel BNC HDCVI high definition video output; Focal Length: 3.6mm fixed lens, Angle of View: H: 89.9° ; Day/Night(ICR), AWB, AGC, BLC, 2DNR; Max. IR LEDs Length: 20m, Smart IR; Power Supply: DC12V±20%, Power Consumption: Max 3.5W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance: Over 500m via 75-3 coaxial cable ; Ingress Protection: IP67 ; Material: Plastic	19€ 17.5 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

17.		2MP Waterproof HDCVI IR-Bullet Camera DAHUA DH-HAC-HFW1200SP Image Sensor: 1/2.7" 2Megapixel CMOS ; Effective Pixels: 1930(H)×1088(V); Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@1080P ; Min. Illumination: 0.02Lux/F2.0, 0Lux IR on; Max. IR LEDs Length: 30m, Smart IR ; Focal length: 3.6mm, Angle of View: H: 89.9°; Power Supply: DC12V±20%, Power Consumption: Max 3.6W ; Working Environment: -30°C~+60°C, Less than 95%RH (no condensation); Transmission Distance: Over 500m via 75-3 coaxial cable ; Ingress Protection: IP67 ; Material: Metal (body); With bracket	29€ 26 €
18.		2.4MP Waterproof HDCVI Camera DAHUA DH-HAC-HFW2220EP Image Sensor: 1/2.8" 2.4Megapixel CMOS; Effective Pixels: 1984(H)×1225(V); Electronic Shutter: 1/3s~1/100,000s; Min. Illumination: 0.05Lux@F1.2(AGC ON), 0Lux IR on; Video Frame Rate: 25/30/50/60fps@720P; 25/30fps@1080P; Video Output 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch); Focal Length: 3.6mm, Angle of View H: 88°; OSD Menu, control over coaxial cable; DWDR, Day/Night(ICR), AWB, AGC, BLC, 3D-DNR; Max. IR LEDs length 40m, Smart IR; Power Supply: DC12V±20%; Power Consumption: Max 5.5W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance Over 500m via 75-3 coaxial cable; Ingress Protection: IP67; Material: Metal; With bracket	28 €
19.		2MP Waterproof HDCVI IR-Bullet Camera DAHUA DH-HAC-HFW1200DP Image Sensor: 1/2.7" 2Megapixel CMOS; Effective Pixels: 1930(H)×1088(V); Electronic Shutter: 1/50s~1/100,000s; Video Frame Rate: 25fps@1080P; Synchronization: Internal; Min. Illumination: 0.01Lux@F1.2(AGC ON), 0Lux IR on; Video Output: 1-channel BNC HDCVI high definition video output. Max. IR LEDs Length: 80m, Smart IR; Day/Night: Auto(ICR) / Color / B/W; Noise Reduction: 2D. Focal length: 3.6mm ; Angle of View: H: 59.4°(89.9°/ 41.4° / 26.5° / 20.6°); Mount Type: M12; Power Supply: DC12V±20%;Power Consumption: Max 5W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance: Over 500m via 75-3 coaxial cable; Ingress Protection: IP67; Dimensions(W×D×H): 241.8mm×90.2mm×83.7mm; Weight: 0.64kg; Material: Metal (front) + Plastic (body) ; With bracket	36€ 32 €
20.		2MP Waterproof HDCVI IR-Bullet Camera DH-HAC-HFW1200RP-VF Image Sensor: 1/2.7" 2Megapixel CMOS ; Effective Pixels: 1930(H)×1088(V) ; Electronic Shutter: 1/50s~1/100,000s ; Video Frame Rate: 25fps@1080P; Mini. Illumination: 0.01Lux@F1.2(AGC ON), 0Lux IR on; Video Output: 1-channel BNC HDCVI high definition video output ; Focal Length: 2.7~12mm, Angle of View: H: 109°~35° ; Max. IR LEDs Length: 30m, Smart IR ; Day/Night: Auto(ICR) / Color / B/W ; Noise Reduction: 2D ; Power Supply: DC12V±20% ; Power Consumption: Max 3.8W ; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation) ; Transmission Distance: Over 500m via 75-3 coaxial cable ; Ingress Protection: IP67 ; Material: Metal ; With bracket	44€ 43 €
21.		4MP HDCVI WDR IR Bullet Camera DAHUA DH-HAC-HFW2401SP Image Sensor: 1/3" CMOS; Effective Pixels: 2688(H)×1520(V), 4.1MP; Electronic Shutter Speed: 1/3s~1/300,000s; Minimum Illumination: 0.03Lux/F1.5, 0Lux IR on; S/N Ratio More than 65Db; IR Distance Up to 30m; Focal Length: 3.6mm, Angle of View H: 78°; Resolution: 4MP (2560×1440); Frame Rate: 25fps@4MP; Day/Night Auto (ICR) / Manual; 120dB True WDR, 3DNR; BLC / HLC / WDR; Power Supply: 12V DC ±25%; Power Consumption: Max 7W (12V DC, IR on); Ingress Protection & Vandal Resistance: IP67 ; With bracket	59€ 55.9 €
22.		4MP HDCVI WDR IR Bullet Camera DAHUA DH-HAC-HFW2401DP Image Sensor: 1/3" CMOS; Effective Pixels: 2688(H)×1520(V), 4.1MP; Electronic Shutter Speed: 1/3s~1/300,000s; Minimum Illumination: 0.03Lux/F1.5, 0Lux IR on; S/N Ratio More than 65Db; IR Distance Up to 80m; Focal Length: 3.6mm, Angle of View H: 78°; Resolution: 4MP (2560×1440); Frame Rate: 25fps@4MP; Day/Night Auto (ICR) / Manual; 120dB True WDR, 3DNR; BLC / HLC / WDR; Power Supply: 12V DC ±25%; Power Consumption: Max 7W (12V DC, IR on); Ingress Protection & Vandal Resistance: IP67 ; With bracket	65€ 62 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

23.		2.4MP HDCVI camera DAHUA DH-HAC-HFW2220RP-VF GenII Image Sensor 1/2.8" 2.4Megapixel CMOS ; Effective Pixels 1984(H)×1225(V) ; Video Frame Rate 25/30/50/60fps@720P ; 25/30fps@1080P ; Focal Length 2.7~12mm ; Mini.Illumination 0.05Lux@F1.2(AGC ON) , 0Lux IR on ; Video Output 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch); Max. IR LEDs Length 30m Smart IR ; Day/Night Auto(ICR) / Color / B/W; Noise Reduction 2D/3D; OSD Menu ; Power Supply DC12V±10%; Working Environment -30°C~+60°C; Ingress Protection: IP66; With bracket	83€ 79.5 €
24.		2.4MP HDCVI Box Camera DAHUA DH-HAC-HF3220E Image Sensor: 1/2.8" 2.4Megapixel CMOS ; Effective Pixels: 1984(H)×1225(V); Electronic Shutter: 1/3s~1/100,000s; Video Frame Rate: 25/30/50/60fps@720P; 25/30fps@1080P; Min. Illumination: 0.05Lux/F1.4; Video Output: 1-channel BNC HDCVI high definition video output / CVBS standard definition video output (Can switch); High speed, long distance real-time transmission; HD and SD switchable, Tester out; OSD Menu , control over coaxial cable; DWDR, Day/Night(ICR), AWB, AGC, BLC, 3DNR, Auto Iris; Power Supply: AC24V±10% / DC12V±10%; Power Consumption: Max 6W; Working Environment: -30°C~+60°C / Less than 95%RH (no condensation); Transmission Distance: Over 500m via 75-3 coaxial cable ; Material: Metal; Without lens and bracket	87 €
25.		2.4MP Waterproof HDCVI Camera DAHUA DH-HAC-HFW3220EP-ZH Image Sensor: 1/2.8" 2.4Megapixel CMOS ; Effective Pixels 1984(H)×1225(V); Electronic Shutter: 1/3s~1/100,000s; Mini.Illumination: 0.05Lux@F1.2(AGC ON), 0Lux IR on; Video Frame Rate 25/30/50/60fps@720P; 25/30fps@1080P ; Video Output 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch); Mini.Illumination: 0.05Lux@F1.2(AGC ON), 0Lux IR on; Focal Length: 2.7~12mm; Lens Type: Motorized/Auto Iris ; Alarm: 1 channel in/out; Audio: 1 channel in; Max. IR LEDs Length: 50m, Smart IR ; OSD Menu, control over coaxial cable; Day/Night(ICR), AWB, AGC, BLC, 3D-DNR; Power Supply: AC24V±10%; Power Consumption: Max 13W; Working Environment: -40°C~+60°C / Less than 95%RH (no condensation); Transmission Distance: Over 300m via 75-3 coaxial cable; Ingress Protection: IP66	88 €
26.		2MP PTZ HDCVI Camera DAHUA DH-SD50225I-HC Image Sensor: 1/2.8" Exmor R CMOS ; Effective Pixels: 1920(H) x 1080(V), 2 Megapixels; Electronic Shutter Speed: 1/3s~1/300,000s; Minimum Illumination Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6; S/N Ratio: More than 55dB; Focal Length: 4.8mm~120mm; Angle of View H: 59.2° ~ 2.4° ; Focus Control: Auto/Manual; Optical Zoom: 25x; Digital Zoom: 16x ; Flip: 180°; Privacy Masking: Up to 24 areas; Pan/Tilt Range Pan: 0° ~ 360° endless; Tilt: 0° ~ 90°, auto flip 180°; Manual Control Speed Pan: 0.1° ~ 350°/s; Tilt: 0.1° ~ 250°/s; Preset Speed Pan: 500°/s; Tilt: 500°/s; Presets: 300; PTZ Mode: 5 Pattern, 8 Tour, Auto Pan, Auto Scan; Protocol: DH-SD, Pelco-P/D (Auto recognition); Video Resolution: 1080P(1920×1080) / 720P(1280×720); Frame Rate: 25/30fps@1080P, 25/30/50/60fps@720P; Video Output: 1-channel BNC HDCVI high definition video output/CVBS standard definition video output (switchable); Day/Night: Auto(ICR) / Color / B/W; 120dB true WDR, 3D DNR; Video Interface: 1; Audio Interface: 1/1; RS485: 1; Alarm: 2/1; Ingress Protection: IP67; Vandal Resistance: IK10 ; Power Supply: AC24V/1.5A(±10%); Power Consumption: 13W, 23W (Heater on); Casing: Metal	210€ 190 €
27.		2MP PTZ HDCVI Camera DAHUA DH-SD59220I-HC Image Sensor 1/2.8" Exmor CMOS ; Effective Pixels: 1920(H) x 1080(V) , 2Megapixels ; Resolution 25/30fps@1080P, 25/30/50/60fps@720P ; Audio 1 channel In; Electronic Shutter Speed 1/1 ~ 1/30,000s; Min. Illumination Color: 0.05Lux@F1.6; B/W: 0.005Lux@F1.6; 0Lux (IR on); IR Distance 100m; Focal Length: 4.7mm ~ 94mm; 20x Optical zoom, 16x Digital Zoom ; Pan/Tilt Range Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°, auto flip 180°; Protocol DH-SD, Pelco-P/D (Auto recognition); OSD ; Video Output: 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch); Day/Night Auto(ICR) / Color / B/W; BLC / HLC / DWDR (Digital WDR), White Balance Auto, ATW, Indoor, Outdoor, Manual; Noise Reduction 2D/3D; RS485 x 1; Alarm 2/1 channel In/Out; Power	330€ 299 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

28.		Supply: AC24V/3A (±10%); Working Environment: -40°C ~ 70°C; Ingress Protection: IP66 2MP PTZ HDCVI Camera DAHUA DH-SD6C220I-HC Image Sensor: 1/2.8" Exmor CMOS; Electronic Shutter Speed: 1/1 ~ 1/30,000s; Effective Pixels: 1920(H) x 1080(V), 2Megapixels; Min. Illumination: Color: 0.05Lux@F1.4; B/W: 0.005Lux@F1.4; 0Lux (IR on); S/N Ratio: More than 50Db; Resolution: 25/30fps@1080P, 25/30/50/60fps@720P; Video Output: 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch); DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus; Control over coaxial cable, long distance real-time transmission; Focal Length: 4.7mm~94mm, Angle of View: H: 54.1° ~ 3.2°; 20x Optical zoom, Digital Zoom: 16x; IR Distance up to 100m; Max 240°/s pan speed, 360° endless pan rotation; Up to 300 presets, 5 auto scan, 8 tour, 5 pattern; Built-in 2/1 alarm in/out; Support intelligent 3D positioning with DH-SD protocol; RS4851; Alarm 2/1 channel In/Out; Power Supply: AC 24V/3A (±10%); Power Consumption: 10.5W, 26W (IR on, Heater on); Working Environment: -40°C ~ 60°C / Less than 90% RH; Ingress Protection: IP66	440 € 390 €
UTC Controller			
29.		UTC Controller PFM820 Supports different formats (HDCVI/AHD/HDTVI/CVBS) switch, which is to satisfy the requirements of different storage device environments for clients. Various format indicator lights, which makes it convenient for users to check the current format status and prompt if the format switch is successful. Power Consumption: 0.3W; Power Supply AAA battery*2; Indicator Lights: prompt current format;	15 €
TESTER			
30.		Tester DAHUA DH-PFM905 Function Port: 2*BNC port (video in and video out), 1*RS485, 1*Micro USB, 1*Audio In, 1*Reset, 1*12V/1A output, 1*charge input; Support HDCVI/ AHD/ HDTVI/ CVBS analog self-adaptive access and switch; Resolution: 720P25fps, 720P30fps, 720P50fps, 720P60fps, 1080P25fps, 1080P30fps; Camera Test: Real time video, PTZ control, audio test, full screen preview and 8x digital zoom, snapshot, record video(H.264); Audio Test: 1 channel audio in; Support audio and RS485 control; Screen: 4.0 inch TFT 800*RGB*480(WVGA) resolution, 16.7M color, backlight brightness adjustable; Operation Method: 10 control keys; Support DC12V/1A longer power supply; Support video screen shot, video recording, record playback and data monitor; Protocol: More than 30 protocols including Dahua, Pelco-D/P, Samsung, Panasonic, Lillin, Yaan etc; Reading port: Micro USB (USB mass storage); Capacity: 8GB flash (internal); Charger: Input: 100V-240V~50/60Hz, Output: 12V/1A, Φ5.5mm(0.22"); Battery: Standard dischargeable 7.4V Li battery, 10.4Wh capacity, and working time can be about 5 hours	195 €
МЕГАПИКСЕЛНИ IP КАМЕРИ			
31.		3MP IR Eyeball Network Camera DAHUA IPC-HDW1320SP Image Sensor: 1/3" 3Megapixel progressive scan CMOS; Electronic Shutter Speed: Auto/Manual, 1s~1/100000s; Min. Illumination: 0.1Lux/F2.0(Color), 0Lux/F2.0(IR on); S/N Ratio: More than 50dB; Focal Length: 3.6mm, Angle of View: H: 81°; DWDR, 3DNR, AWB, Day/Night(ICR), AGC, BLC; IR Distance up to 30m; Compatibility: ONVIF, PSIA, CGI; Ethernet: RJ-45 (10/100Base-T); Max. User Access: 20 users; Power Supply: DC12V PoE (802.3af); Power Consumption: <4W(IR on); Working Environment: -30°C~+60°C, Less than 95% RH; Ingress Protection: IP67	75 € 65 €
32.		3MP HD Network Mini IR Bullet Camera DAHUA DH-IPC-HFW1320SP Image Sensor: 1/3" 3Megapixel progressive scan CMOS; Effective Pixels: 2048(H) · 1536(V); Electronic Shutter Speed: Auto/Manual, 1s~1/100000s; Min. Illumination: 0.045Lux/F2.1(Color), 0Lux/F2.1(IR on); S/N Ratio: More than 50dB; Focal Length: 3.6mm, Angle of View: H: 81°; Max. IR LEDs Length 30m; Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF, CGI; Compression: H.264/H.264H/ H.264B/ MJPEG; Resolution: 3M(2048× 1536)/1080P(1920× 1080)/720P(1280× 720)/ D1(704× 576/704× 480) /CIF(352× 288/352×	75 € 66 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

		240); Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Power Supply: DC12V, PoE (802.3af); Power Consumption <4.7W(IR on); Working Environment: -30°C~+60°C, Less than 95% RH; Ingress Protection: IP67 ; Vandal Resistance: N/A; Dimensions: Ø70mm×165mm; Weight: 0.38Kg(with package 0.44 Kg)	
33.		3MP IR Mini-Dome Network Camera DAHUA DH-IPC-HDBW1320EP Image Sensor: 1/3" 3Megapixel progressive CMOS ; Minimum Illumination: 0.1Lux/F2.0 (Color), 0Lux/F2.0(IR on); IR Distance up to 30m; Focal Length: 2.8 mm; Angle of View: H:98°, V:51° ; Resolution: 3M(2048×1536)(2304×1296) / 1080P(1920×1080) / 1.3M(1280×960) 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240); DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS; Digital Zoom: 16x; Ethernet: RJ-45 (10/100Base-T); Interoperability: ONVIF , PSIA, CGI; Power Supply: DC12V PoE (802.3af)(Class 0); Operating Conditions: -30°C ~ +60°C; Ingress Protection: IP67 , Vandal Resistance: IK10	67 €
34.		4MP Dome Camera DAHUA DH-IPC-HDW4421EP Image Sensor: 1/3" 4Megapixel progressive scan CMOS ; Effective Pixels: 2688(H)×1520(V); Electronic Shutter Speed: Auto / Manual, 1/3(4)~1/100000s; Min. Illumination: 0.01Lux/F2.0 (Color), 0Lux/F2.0(IR on); S/N Ratio: More than 50dB; Focal Length: 3.6mm; Angle of View: H:81° ; Max. IR LEDs Length: 50m ; Day/Night: Auto(ICR)/Color/B/W; Backlight Compensation: BLC/HLC/WDR(120dB); White Balance: Auto/Sunny/Night/Outdoor/Customized; Gain Control: Auto/Manual; Noise Reduction: 3D; Privacy Masking: Up to 4 areas; Resolution: 4M (2688×1520) / 4M (2560×1440) / 3M (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (7040×576/704×480) / CIF (352×288/352×240); Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF , PSIA, CGI; Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Power Supply: DC12V, PoE (802.3af); Power Consumption: Max 4.9W; Working Environment: -30°C~+60°C, Less than 95% RH; Ingress Protection: IP67	80 € 75 €
35.		4MP Vandalproof Dome Camera DAHUA DH-IPC-HDW4431EMP-AS Image Sensor: 1/3" 4Megapixel progressive scan CMOS ; Effective Pixels: 2688(H) x 1520(V); Electronic Shutter Speed: Auto/Manual, 1/3(4)~1/100000s; Min. Illumination: 0.01Lux/F2.0 (Color), 0Lux/F2.0(IR on); S/N Ratio: More than 50dB; Max. IR LEDs Length: 50m ; WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC; Privacy Masking: Up to 4 areas; Focal Length 2.8mm, Angle of View: 104°; Built-in Microphone ; Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF , PSIA, CGI; Max. User Access: 20 users; Smart Phone iPhone, iPad, Android, Windows Phone; Memory Slot: Micro SD Max 128GB ; Ingress Protection: IP67 ; Power Supply: DC12V, PoE (802.3af); Power Consumption: Max 5W; Working Environment: -30°C ~ +60°C	105 € 99 €
36.		1.3MP HD Wi-Fi PT Camera DAHUA DH-IPC-A15 Image Sensor: 1/3" 1.3Megapixel CMOS ; Effective Pixels: 1280(H)×960(V); Electronic Shutter Speed: Auto/Manual, 1/3(4)s~1/30000s; Min. Illumination: 0.01lux/F2.0(color), 0lux/F2.0(IR on); S/N Ratio: More than 50dB; IR distance: 10m ; Day/Night: Auto(ICR) / Color / B/W; BLC/HLC/DWDR, Noise Reduction: 3D; Focal Length: 3.6mm, Angle of View: H:72° ; Pan/ Tilt Range: Pan: 0°~355°; Tilt: 0°~90°; Preset Speed: 100°/s; Preset: 25, Tour: 8; Resolution: 1.3MP/720P/VGA/QVGA ; Interface: Built-in Mic & Speaker ; Ethernet: RJ-45 (10/100Base-T); Wi-Fi: Wi-Fi (IEEE802.11b/g/n), 50m(open field); Compatibility: ONVIF , CGI; Max. User Access: 20 users; Memory Slot: Micro SD, up to 128GB ; Power Supply: DC 5V2A; Power Consumption: <8.2W; Working Environment: -10°C~+45°C, Less than 95%RH	119 €
37.		3MP HD Network IR Bullet Camera DAHUA DH-IPC-HFW2320RP-ZS-IRE6 Image Sensor: 1/3" 3Megapixel progressive scan CMOS ; Effective Pixels: 2304(H) x 1296(V); Electronic Shutter Speed: Auto/Manual, 1/3(4)~1/100000s; Min. Illumination: 0.1Lux/F1.4 (Color), 0Lux/F1.4(IR on); S/N Ratio: More than 50dB; Max. IR LEDs Length: 60m ; DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC; Privacy Masking: Up to 4 areas; Focal Length: 2.7mm~12mm, Angle of View: H: 92°~ 28° ; Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF , CGI, PSIA; Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Memory Slot: Micro SD, Max 128GB ; Ingress Protection: IP67;	133 € 123 €

Satel
Intelligent Security Solutions

DAHUA
TECHNOLOGY



PLANET
Networking & Communication

JVC

BENINCA
TECHNOLOGY TO OPEN

Inova-bg Ltd
SECURITY SYSTEMS

VACRON
ADVANCES IN SECURITY SOLUTIONS

ZHUDELE

Security Vision Systems
MOBOTIX

cofem, s.a.
1973

ACTi
Connecting Vision

SAMSUNG

BOSCH

Surveon



WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

		Power Supply: DC12V/ PoE (802.3af)	
38.		4MP Network Camera DAHUA DH-IPC-HFW2431RP-ZS/VFS-IRE6 Image Sensor: 1/3" 4Megapixel progressive scan CMOS ; Effective Pixels: 2688(H)x1520(V); Minimum Illumination: 0.03Lux/F1.4(Color,1/3s,30IRE), 0.3Lux/F1.4(Color,1/30s,30IRE), 0Lux/F1.4(IR on); S/N Ratio: More than 45dB; Focal Length: 2.7mm~13.5mm, motorized lens , Angle of View: H:104°~28°, V:55°~16° ; IR Distance: up to 60m ; 20fps@4M (2688x1520)&25/30fps@3M(2304x1296); WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring: Web viewer, CMS(DSS/PSS)&DMSS; Micro SD card slot, up to 128GB ; Digital zoom: 16X ; Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF , PSIA, CGI; Power Supply: DC12V, PoE (802.3af); Working Environment: -30°C~+60°C; Ingress Protection: IP66 ; Casing: metal	HOBO!!! 125 €
39.		3MP Water-Proof & Vandal-Proof Camera DAHUA DH-IPC-HDBW2300RP-Z Image Sensor: 1/3" 3Megapixel progressive scan Aptina CMOS ; Effective Pixels: 2048(H)x1536(V); Min. Illumination: 0.1Lux/F1.4 (Color), 0.01Lux/F1.4(B/W); 0Lux/F1.4(IR on); S/N Ratio: More than 50dB; Focal Length: 2.8mm~12mm, Angle of View H: 92°~28° ; Lens Type: Motorized/Fixed Iris ; Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF , PSIA, CGI; Max. IR LEDs Length: 20m ; Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Power Supply: DC12V, PoE (802.3af); Power Consumption: <8.5W; Working Environment: -30°C~+60°C, Less than 95% RH; Ingress Protection: IP66 ; Vandal Resistance: IK10	140 €
40.		4MP Vandalproof Fisheye Camera DAHUA DH-IPC-EB5400P Image Sensor: 1/3" 4Megapixel progressive scan CMOS ; Effective Pixels: 2592(H)x1520(V); Electronic Shutter Speed: Auto/Manual 1/3(4)~1/10000; Min. Illumination: 0.01Lux/F2.0(color), 0.001Lux/F2.0(B/W); S/N Ratio: More than 50Db; Focal Length: 1.18mm ; Angle of View: H:180° ; Day/Night: Auto(Electronic) / Color / B/W; Backlight Compensation: BLC/HLC/DWDR; White Balance: Auto/Manual; Noise Reduction: 3D; Privacy Masking: Up to 4 areas; Compression: H.264/ MJPEG; Resolution: 4M(2592x1520) / 3M(2048x1520) / UXGA(1600x1200) / 1.3M(1280x960) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240) ; Interface: 1/1 channel In/Out(Built in Microphone) ; Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF ,PSIA,CGI; Max. User: Access 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Memory Slot: Micro SD, Max 64GB ; Alarm: 1/1 channel In/Out; Power Supply: DC12V, PoE ; Power Consumption: Max 6W; Working Environment: -30°C~+60°C, Less than 95% RH; Ingress Protection: N/A; Vandal Resistance: IK10	160 €
41.		1MP Pinhole Camera DAHUA DH-IPC-HUM8101P Image Sensor: 1/3" 1.3Megapixel progressive scan CMOS ; Effective Pixels: 1280(H)x960(V); Electronic Shutter Speed: Auto/Manual, 1/3~1/10000s; Min. Illumination: 0.01Lux/F2.8 (Color), 0.001Lux/F2.8(B/W); S/N Ratio: More than 50Db; Day/Night: Auto (Electronic) / Color /B/W; Backlight Compensation: BLC / HLC/WDR(100dB); White Balance: Auto/Manual; Gain Control: Auto/Manual; Noise Reduction: 3D; Privacy Masking: Up to 4 areas; Focal Length: 3.7mm ; Max Aperture: F2.8; Focus Control: Manual; Angle of View: 77°; Compression: H.264/MJPEG; Resolution: 1.3M(1280x960)/720P(1280x720)/D1(704x576) /CIF(352x288); Ethernet: RJ-45 (10/100/1000Base-T); Compatibility: ONVIF , PSIA,CGI; Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Memory Slot: Micro SD, Max 64GB; RS485: 1 port; Alarm: 1/1 channel In/Out; Power Supply: DC12V, PoE (802.3af); Power Consumption: Max 7W; Working Environment: -30°C~+60°C, Less than 95% RH	230 € 210 €
42.		4MP Bullet Camera DAHUA IPC-HFW5431EP-Z Image Sensor: 1/3"4Megapixel progressive scan CMOS ; Electronic Shutter Speed: Auto/Manual, 1/3s~1/100000s; Min. Illumination: 0.03 lux(Color) / 0 lux (IR on); Focal Length: 2.7mm ~12mm motorized lens, Angle of View: H100°~34° ; Day/Night:Auto(ICR) / Color /B/W; Backlight Compensation: BLC / HLC / DWDR; Privacy Masking: Up to 4 areas; Max. IR LEDs Length: 50m ; Smart Phone: iPhone, iPad, Android, Windows Phone; Memory Slot: Micro SD, Max 128GB ; Power Supply: DC12V, PoE ; Working Environment: -30°C~+60°C;	240 €

Satel
Intelligent Security Solutions

DAHUA
TECHNOLOGY



PLANET
Networking & Communication

JVC

BENINCA
TECHNOLOGY TO OPEN

Inova-bg Ltd
SECURITY SYSTEMS

VACRON
ADVANCES IN SECURITY SOLUTIONS

ZHUDELE

Security Vision Systems
MOBOTIX

cofem, s.a.
1973

ACTi
Connecting Vision

SAMSUNG

BOSCH

Surveon



WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

		Ingress Protection: IP67	
43.		4K Dome Camera DAHUA DH-IPC-HDBW4800EP Image Sensor: 1/2.3" 4K progressive scan CMOS ; Electronic Shutter Speed: Auto/Manual, 1/3(4)~1/10000s; Effective Pixels: 3840(H)x2160(V) ; Min. Illumination: 0.1Lux/F1.6 (Color), 0Lux/F1.8(IR on); S/N Ratio: More than 50dB; Max. IR LEDs Length: 20m ; Day/Night: Auto(ICR)/Color/B/W; Backlight Compensation: BLC / HLC / DWDR; White Balance: Auto/Manual; Gain Control: Auto/Manual; Noise Reduction: 3D; Privacy Masking: Up to 4 areas; Focal Length: 4mm ; Angle of View: H: 80°; Video Compression: H.264/ MJPEG; Resolution: 4K(3840x2160) / 1080P (1920x1080) / 720P(1280x720) / D1(704x576/704x480) / CIF(352x288/352x240); Ethernet: RJ-45 (10/100Base-T); Compatibility: ONVIF , PSIA, CGI; Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Power Supply: DC12V, PoE (802.3af); Power Consumption: <7W; Working Environment: -30°C~+60°C, Less than 95% RH; Ingress Protection: IP66 ; Vandal Resistance: IK10	375-€ 365 €
44.		3MP Bullet Network Camera DAHUA IPC-HFW8331E-Z5 Image Sensor: 1/2.8" 3Megapixel progressive scan CMOS ; Effective Pixels: 2048(H)x1536(V); Minimum Illumination: 0.005Lux/F1.4(Color), 0Lux/F1.4(IR on); S/N Ratio: More than 50dB; IR Distance: up to 100m ; IR On/Off Control: Auto/ Manual, 4 IR LEDs; WDR(140dB),Day/Night (ICR), 3DNR, AWB, AGC, BLC; Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS; Lens Type: Motorized /Auto Iris(HALL); Focal Length: 7~35mm motorized , Angle of View: H: 32°~11°, V:23.8°~8.6°, Optical Zoom: 5x; Digital Zoom: 16x; Focus Control: Motorized; Ethernet: RJ-45 (100/1000Base-T); Interoperability: ONVIF , PSIA, CGI; Edge Storage: NAS, Local PC for instant recording, Micro SD card 128GB; Power Supply: DC12V, PoE (802.3at)(Class 4); Power Consumption: <13W; Ingress Protection: IP67 , Vandal Resistance: IK10 ; Operating Conditions: -40°C ~ +60°C; Casing: Metal	420 €
45.		2MP 25x Starlight IR PTZ Network Camera DAHUA DH-SD49225T-HN Image Sensor: 1/2.8" STARVIS™ CMOS ; Effective Pixels: 1920(H) x 1080(V), 2MP; Electronic Shutter Speed: 1/1s~1/300,000s; Minimum Illumination Color: 0.005Lux@F1.6; 0Lux@F1.6 (IR on); IR Distance up to 100m ; IR LEDs: 6; Focal Length: 4.8mm~120mm , Angle of View: H: 59.2° ~ 2.4°; Powerful 25x optical zoom ; Digital Zoom: 16x ; Support H.265&H.264 Triple-streams encoding; Max. 50/60fps@1080P, 25/30/50/60fps@720P; Day/Night: Auto(ICR) / Color / B/W; BLC / HLC / WDR(120dB), Ultra DNR (2D/3D); Support Motion Detection; Support Defog; Pan/Tilt Range: Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°,auto flip 180°; Manual Control: Speed Pan: 0.1° ~200° /s; Tilt: 0.1° ~120° /s; Preset Speed: Pan: 240° /s; Tilt: 200° /s; Presets: 300; Ethernet: RJ-45 (10/100Base-T); Interoperability: ONVIF , PSIA, CGI; Power Supply: DC 12V/3A, PoE+ (802.3at); Power Consumption: 13W,20W (IR on); Operating Conditions: -40°C ~ 70°C; Ingress Protection: IP66 ; Casing: Metal	290 €
46.		2MP 30x Starlight IR PTZ Network Camera DAHUA DH-SD6C230U-HNI Image Sensor: 1/2.8" STARVIS™ CMOS ; Effective Pixels: 1920(H) x 1080(V), 2MP; Electronic Shutter Speed: 1/1s~1/300,000s; Minimum Illumination: Color: 0.005Lux@F1.6; 0Lux@F1.6 (IR on); S/N Ratio: More than 55Db; IR Distance up to 150m ; IR LEDs: 6; Focal Length: 4.5mm~135mm , Angle of View: H: 67.8° ~ 2.4°; Optical Zoom: 30x ; Digital Zoom: 16x ; Pan/Tilt Range: Pan: 0° ~ 360° endless; Tilt: -15° ~ 90°,auto flip 180°; Presets: 300; Max. 50/60fps@1080P, 25/30/50/60fps@720P; Auto-tracking and IVS; Day/Night: Auto(ICR) / Color / B/W; BLC / HLC / WDR(120dB), Ultra DNR (2D/3D); Support Motion Detection; Support Defog; Ethernet: RJ-45 (10/100Base-T); Power Supply: AC24V/3A(±10%); Operating Conditions: -40°C ~ 60°C; Ingress Protection: IP66 ; Casing: Metal	640 €
47.		3MP PTZ Camera DAHUA DH-SD65320-HN Image Sensor: 1/3" CMOS ; Effective Pixels: 2048(H) x 1536(V), 3 Megapixels; Min. Illumination: Color: 0.05Lux@F1.6,B/W: 0.005Lux@F1.6; Electronic Shutter Speed: 1/1 ~ 1/30,000s; S/N Ratio: More than 50dB; Focal Length: 4.7mm ~ 94.0mm (20x Optical zoom); Video Output: BNC(1.0Vp-p/75Ω); Powerful 20X optical zoom , Digital Zoom: 16X ; WDR, Day/Night(ICR), DNR (2D&3D),Auto iris, Auto focus, AWB, AGC,BLC; Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS; Max 400 °/s pan speed, 360° endless pan rotation; Up to 255 presets, 5 auto scan, 8 tour, 5 pattern; Built-in 7/2 alarm in/out;	770-€ 670 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



		Resolution: 3M(2048·1536)/1080P(1920×1080)/720P(1280×720)/D1(704×576/704×480)/CIF(352×288/352×240); Ethernet: RJ-45 (10/100Base-T); Protocol: IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour; ONVIF: ONVIF Profile S ; Max. User Access: 20 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Memory Slot: Micro SD, Max 64GB ; RS485: 1; Alarm: 7/2 channel In/Out; Ingress Protection: IP67 ; Power Supply: AC 24V/3A (±10%), Power Consumption 15W, 40W(Heater on); Working Environment: -40°C ~ 60°C, Less than 90% RH	
ANTENNA			
48.		Antenna DAHUA PFM881 Working Frequency ETSI: 5.15~5.35 GHz, 5470~5725 MHz ISM band ; Modulation Mode 802.11 a/n: OFDM; Built-in antenna : gain 15dBi ; Receiving Sensitivity -74dBm @ 65Mbps, -96dBm@1Mbps; Optimal Transmission Distance 0-5KM; Working Frequency Band 5470-5825 MHz; Wireless Direction Angle: Horizontal 40°, vertical 15°; Power Module Port: 1*POE RJ45(IN: 220V, OUT: 24V/0.5A), 1*LAN RJ45; Power Consumption MAX 8W; Port 1*POE RJ45, 1*LAN RJ45; Working Temperature -30°C~+70°C; Network Mode Route/Network Bridge; Working Mode Access Point/Client/WDS AP/WDS client/WDS Repeater ; Network Protocol TCP/UDP/ARP/ICMP/DHCP/HTTP/NTP; Support webpage configuration; Long-Distance Communication Throughput Rate: ≤30Mbps@5km; Bandwidth Flexible Configuration: 5M/10M/20M/40MHz	113 €
SWITCH			
49.		Desktop Switch DAHUA PFS3005-4P-58 4-Port 10/100Mbps 802.3af/at PoE + 1-Port 10/100Mbps Ethernet Port 1*10/100 Base-T, 4*10/100 Base-T(PoE power supply); Each power ≤30W; Switching Capacity 1Gbps; Power Default DC51V/1.25A power adapter; Working Temperature -10°C~50°C, Dimension 100mm×100mm×26mm.	26 €
50.		4-Port PoE Switch DAHUA DH-PFS3106-4P-60 Two-layer industrial POE switch; MAC auto study and aging, MAC address list capacity is 8K; Ethernet port: 1*100/1000 Base-X, 1*10/100/1000 Base-T, 4*10/100 Base-T(PoE power supply); PoE power consumption: Each power ≤30W, Total≤60W; PoE protocol: IEEE802.3af, IEEE802.3at; Exchange mode: Store & forward; Application Humidity: 10%—90%; Power Default: DC53V power adapter; Working temperature: -30°C~65°C	30 €
51.		24-Port PoE Switch DAHUA DH-PFS4226-24ET-240 Layer 2 management PoE switch; PoE budget: 240W; Support PoE, PoE+, Hi-PoE; 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300); 250 meters long distance PoE transmission; PoE management, PoE Setting/Event Statistics/Green PoE; Search and upgrade via ConfigTool; Support Web management; High lightning protection design; Non-blocking video transmission	HOBO!!! 180 €
ДИГИТАЛНИ ВИДЕО РЕКОРДЕРИ (DVRs)			
52.		8CH All Channel 960H DVR DAHUA DH-DVR5108C-V2 Up to 8 cameras with 1080p realtime preview; H.264 dual-stream video compression; Video input: 8 channel BNC; HDMI/VGA/TV simultaneous video output ; Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768, 800×600; OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording; Recording Resolution: 960H/D1/4CIF(704×576 / 704× 480) / CIF(352×288/ 352×240) / QCIF(176×144/176×120) ; Backup Mode: USB Device / Network / Internal SATA burner; Ethernet: RJ-45 port (10/100M); Max. User Access: 128 users; Smart Phone: iPhone, iPad, Android, Windows Phone; Internal HDD: 1 SATA port, up to 4TB(No HDD Included) ; USB Interface: 2 ports (1 Rear), USB2.0; RS485 PTZ control; 3D intelligent positioning with Dahua PTZ dome camera; Power Supply: DC12V/2A; Working Environment: -10°C ~+55°C /10%~90%RH / 86~106kpa; Dimension (W×D×H): Mini 1U, 325mm×245mm×45mm	60 € 58 €

Satel
Intelligent Security Solutions

dahua
TECHNOLOGY



PLANET
Networking & Communication

JVC

BENINCA
TECHNOLOGY TO OPEN

Inova-bg Ltd
SECURITY SYSTEMS

VACRON
ADVANCES IN SECURITY SOLUTIONS

ZHUDELE

Security Vision Systems
MOBOTIX

cofem, s.a.
1973

ACTi
Connecting Vision

SAMSUNG

BOSCH

Surveon



WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



53.		16CH 2CIF DVR DAHUA DH-DVR2116C-W(V2) Video Input: 16 channel, BNC ; Display Interface: 1 HDMI, 1 VGA, 1TV ; Audio Input: 1 channel, RCA ; Output: 1 channel, RCA ; Two-way Talk: Reuse audio input/output channel 1 ; All channel 2CIF realtime recording ; Privacy Masking: 4 rectangular zones (each camera) ; OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording ; Backup Mode: USB Device / Network / Internal SATA burner ; Ethernet: RJ-45 port (10/100M); Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB Interface: 2 ports (1 Rear), USB2.0 ; RS485: 1 port, For PTZ control ; Power Supply: DC12V/2A ; Power Consumption: 10W(without HDD) ; Working Environment: -10°C ~+55°C	80-€ 78 €
54.		16CH DVR DAHUA 1604HF-A-E Up to 16 Effio cameras with 1080p realtime preview ; Video Input: 16 channel, BNC ; Audio Input: 4 channel ; H.264 dual-stream video compression ; Full channel@960H (960×576 / 960×480) realtime recording ; Display Interface: 1 HDMI, 1 VGA, 1 TV, 1 Spot, BNC (1.0Vp-p, 75Ω); Privacy Masking: 4 rectangular zones (each camera) ; OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording ; Alarm Input: 16channel ; Relay Output: 3 channel ; Backup Mode: USB Device / Network ; Ethernet: RJ-45 port (10/100M/1000M) ; Internal HDD: 2 SATA ports, up to 8TB (No HDD Included) ; USB Interface: 2 ports (1 Rear), USB2.0 ; RS232: 1 port, For PC communication & Keyboard ; RS485: 1 port, For PTZ control ; All channel synchronous realtime playback, GRID interface & smart search ; 3D intelligent positioning with Dahua PTZ dome camera ; Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ; Max. User Access: 20 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Power Supply: DC12V/5A	350 €
55.		24CH All Channel 960H DVR DAHUA DVR7424L Up to 24 cameras with 1080p realtime preview; H.264 dual-stream video compression; Video input 24ch; Audio input 4ch, Output 1ch; Interface 2 HDMI, 1 VGA, 1 TV, 1 Spot ; Backup Mode USB Device/Network/Internal SATA burner/eSATA Device; Ethernet RJ-45 port (10/100/1000M) ; Alarm Input: 16 channel, Alarm Output: 6 channel; Max. User Access 128 users; Smart Phone iPhone, iPad, Android, Windows Phone; Internal HDD: 4 SATA ports, up to 16TB (no HDD included) ; External HDD: 1 eSATA port, up to 16TB ; USB Interface 3 ports (2 Rear), USB2.0; RS232 1 port, For PC communication & Keyboard; RS485 1 port RS485 for PTZ control; Power Supply: DC12V/5A ; Working Environment: -10°C ~+55°C /10%~90%RH / 86~106kpa	450-€ 437 €
56.		32CH All Channel 960H DVR DAHUA DH-DVR7232L 32 cameras with 1080p realtime preview; H.264 dual-stream video compression; Video input 32ch; Audio input 4ch, Output 1ch; Interface 2 HDMI, 1 VGA, 1 TV, 1 Spot ; Backup Mode USB Device/Network/Internal SATA burner/eSATA Device; Ethernet RJ-45 port (10/100/1000M) ; Alarm Input: 16 channel, Alarm Output: 6 channel; Max. User Access 128 users; Smart Phone iPhone, iPad, Android, Windows Phone; Internal HDD: 4 SATA ports, up to 16TB (no HDD included) ; External HDD: 1 eSATA port, up to 16TB ; USB Interface 3 ports (2 Rear), USB2.0; RS232 1 port, For PC communication & Keyboard; RS485 1 port RS485 for PTZ control; Power Supply: DC12V/5A ; Working Environment: -10°C ~+55°C /10%~90%RH / 86~106kpa	550 €
TRIBRID / PENTABRID HDCVI DVRs			
57.		4CH Tribird HDCVI DVR DAHUA DHI-HCVR4104HS-S3 All channel 720P recording ; Input: 4 channel, BNC ; Standard: Analog: PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 4+1 up to 2Mp; Support AHD cameras ; H.264 dual-stream video compression ; Audio Input: 1 channel, RCA , Output: 1 channel, RCA ; Display Interface: 1 HDMI, 1 VGA ; Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768 ; Privacy Masking: 4 rectangular zones (each camera) ; OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording ; ONVIF Version 2.4 conformance ; Ethernet: RJ-45 port (10/100M) ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal HDD: 1 SATA port, up to 6TB (no HDD included) ; USB Interface: 2	43 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



		ports(1 Rear), USB2.0; RS485: 1 port, For PTZ Control ; Power Supply: DC12V/2A; Power Consumption: 10W(without HDD) ; Working Environment: -10°C ~+55°C / 10%~90%RH / 86~106kpa	
58.		4CH Penta-brid DVR DAHUA DHI-XVR4104C Support HDCVI/AHD/TVI/CVBS/IP video inputs; HDCVI Camera Input: 4 Channel; IP Camera Input: 4+1 Channel: each channel up to 2MP; Audio In/Out: 1/1; Resolution: 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Interface: 1 HDMI ,1 VGA; USB: 2 USB Ports (2 USB 2.0); Internal HDD: 1 SATA Port, up to 6TB capacity(No HDD Included); Interface: 1 RJ-45 Port (100M); Max. User Access: 128 users; Smart Phone: iPhone, iPad, Android; Interoperability: ONVIF 2.4.1, CGI Conformant ; Power Supply: DC12V/2A; Power Consumption: <10W (Without HDD); Environmental Operating Conditions: -10°C ~ +55°C, 86 ~ 106kpa	45 €
59.		4CH Tribrid HDCVI DVR DAHUA HCVR5104C-S3 Support 2 x HDCVI or 2 x Analog cameras and 2 IP Video input ; Video Input: 4 channel, BNC ; Analog: 625Line,50f/s, HDCVI: 1080P/720P HDCVI Camera, IP: 1080P/720P/D1/CIF IP Camera ; Support AHD cameras ; All channel 720P realtime or 1080P non-realtime recording ; Audio Input: 1 ch, RCA, Output: 1 channel, RCA ; Two-way Talk: Reuse audio input/output channel 1 ; Display Interface: 1 HDMI, 1 VGA (HDMI/VGA simultaneous video output) ; Resolution: 1920x1080, 1280x1024, 1280x720, 1024x768 ; Recording Video/Audio Compression: H.264/G.711 ; Record Rate: Main Stream: 1080P(1~15fps) / 720P / 960H / D1(1~25/30fps), Extra Stream: CIF/QCIF(1~25/30fps), D1(1~6/7fps) ; ONVIF Version 2.4 conformance ; Internal HDD: 1 SATA port, up to 4TB(No HDD Included) ; USB Interface: 2 ports(2 Rear), USB2.0 ; 3D intelligent positioning with Dahua PTZ dome camera ; ; Backup Mode: USB Device/Internal SATA burner/Network ; Ethernet: RJ-45 port (10/100M) ; Max. User Access: 128 users ; Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone (DMSS) ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Power Supply: DC12V/2A ; Power Consumption: 10W(without HDD) ; Working Environment: -10°C ~+55°C / 10%~90%RH / 86~106kpa	57 € 54 €
60.		4CH Penta-brid 1080P Mini 1U DVR DAHUA DHI-XVR7104H The XVR can auto recognize the signal of front-camera without any setting. It supports up to 4ch of HDCVI/ AHD/TVI/CVBS inputs, and 2ch IP camera each channel up to 5MP; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)720P/960H/D1 /HD1 /BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (1000M); Max. User Access: 128 users; Support IVS (Tripwire/Intrusion/Abandoned/Missing) and Face Detection; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more; USB: 2 USB 2.0 ; RS485 1 Port, for PTZ Control; Internal HDD: 2 SATA Ports, up to 6TB capacity for each disk (no HDD included); Power Supply: DC12V/2A; Power Consumption: <15W (Without HDD)	105 €
61.		4CH 4MP HDCVI DVR DAHUA DHI-HCVR7104H-4M HDCVI/CVBS Auto-detect, the HCVR can auto recognize the signal of front-camera without any setting. HDCVI Camera Input 4 Channel; IP Camera Input: 2 Channel, each channel up to 5MP; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI(up to 3840x2160),1 VGA ; Resolution: 4MP,1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 4MP (115fps)1080P/ 720P/960H/D1/HD1/BCIF/CIF/QCIF(1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps) ; Interoperability: ONVIF 2.4.1, CGI Conformant; Max. User Access: 128 users; Internal HDD: 1 SATA Port, up to 6TB capacity (no HDD included); USB: 2 USB Ports (1 USB 2.0, 1 USB 3.0) ; RS485: 1 Port, for PTZ Control; Support: IVS(Tripwire/ Intrusion/Abandoned /Missing) and Face Detection; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony,	115 € 100 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



		Videotec, Vivotek, and more; Power Supply: DC12V/2A; Power Consumption: <15W (Without HDD); Operating Conditions: -10°C ~ +55°C, 86 ~ 106kpa	
62.		8CH Penta-brid 720P Compact 1U DVR DAHUA DHI-XVR4108HS The XVR can auto recognize the signal of front-camera without any setting. It supports up to 8ch of HDCVI/ AHD/TVI/CVBS inputs, and 2ch IP camera each channel up to 5MP; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)/720P/960H/D1 /HD1 /BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (100M); Max. User Access: 128 users; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more; USB: 2 USB Ports (2 USB 2.0); RS485 1 Port, for PTZ Control; Internal HDD 1 SATA Ports, up to 6TB (no HDD included); Power Supply: DC12V/2A; Power Consumption: <15W (Without HDD)	68-€ 63 €
63.		8CH HDCVI DVR DAHUA HCVR5108HS-S3 Support HDCVI/Analog/IP Video input ; Video Input: 8 channel, BNC ; Analog: PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 8+4 up to 5Mp ; Recording Resolution: 1080P, 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Audio Input: 1 ch, RCA, Output: 1 channel, RCA ; Two-way Talk: Reuse audio input/output channel 1 ; Display Interface: 1 HDMI, 1 VGA ; Interoperability: ONVIF 2.42, CGI Conformant; Internal HDD: 1 SATA Port, up to 8TB capacity(no HDD included); USB Interface: :2 USB Ports (2 USB 2.0); RS485: 1 Port, for PTZ Control; Ethernet: :1 RJ-45 Port (100M); Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android; Third-party Support; Power Supply: DC12V/2A ; Power Consumption: 10W(without HDD) ; Working Environment: -10°C ~+55°C / 10%~90%RH / 86~106kpa	86 €
64.		8CH Penta-brid DVR DAHUA DHI-XVR5108HS The XVR can auto recognize the signal of front-camera without any setting. It supports up to 8ch of HDCVI/ AHD/TVI/CVBS inputs, and 4ch IP camera additionally; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)/720P/960H/D1/HD1 /BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (100M); Max. User Access: 128 users; Support IVS (Tripwire/Intrusion/Abandoned/Missing) and Face Detection; Third-party Support; USB: 2 USB 2.0; RS485 1 Port, for PTZ Control; Internal HDD 1 SATA Ports, up to 6TB (no HDD included); Power Supply: DC12V/2A; Power Consumption: <15W (Without HDD)	98-€ 93 €
65.		8CH Penta-brid 1080P Mini 1U DVR DAHUA DHI-XVR7108H The XVR can auto recognize the signal of front-camera without any setting. It supports up to 8ch of HDCVI/ AHD/TVI/CVBS inputs, and 4ch IP camera each channel up to 5MP; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)/720P/960H/D1 /HD1 /BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (1000M); Max. User Access: 128 users; Support IVS(Tripwire/Intrusion/Abandoned/Missing)and Face Detection; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more; USB: :1 USB 2.0 , 1 USB 3.0; RS485 1 Port, for PTZ Control; Internal HDD: 2 SATA Ports, up to 6TB capacity for each disk (no HDD included); Power Supply: DC12V/2A; Power Consumption:	149 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



		<15W (Without HDD)	
66.		8CH 4MP HDCVI DVR DAHUA DHI-HCVR7108H-4M HDCVI/CVBS Auto-detect, the HCVR can auto recognize the signal of front-camera without any setting. HDCVI Camera Input 8 Channel; IP Camera Input: 2 Channel, each channel up to 5MP; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI(up to 3840x2160),1 VGA ; Resolution: 4MP,1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 4MP(115fps)1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF(1~25/30fps), Sub stream:D1/CIF/QCIF(1~25/30fps) ; Interoperability: ONVIF 2.4.1, CGI Conformant; Max. User Access: 128 users; Internal HDD: 1 SATA Port, up to 6TB capacity (no HDD included); USB: 2 USB Ports (1 USB 2.0, 1 USB 3.0) ; RS485: 1 Port, for PTZ Control; Support: IVS(Tripwire/Intrusion/Abandoned /Missing) and Face Detection; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more; Power Supply: DC12V/2A; Power Consumption: <15W (Without HDD); Operating Conditions: -10°C ~ +55°C, 86 ~ 106kpa	169 € 150 €
67.		16CH Tribird 720P-Lite Compact 1U HDCVI DVR DAHUA DH-HCVR4116HS-S3 All channel 720P recording ; Input: 16 channel, BNC ; Standard: Analog: PAL, HDCVI: 1080P/720P HDCVI Camera, IP: 16+2 up to 5Mp ; Support AHD cameras ; H.264 dual-stream video compression ; Audio Input: 1 channel, RCA, Output: 1 channel, RCA ; Display Interface: 1 HDMI, 1 VGA ; Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768 ; Privacy Masking: 4 rectangular zones (each camera) ; OSD: Camera title, Time, Video loss, Camera lock, Motion detection, Recording ; ONVIF Version 2.4 conformance ; Ethernet: RJ-45 port (10/100M) ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal HDD: 1 SATA port, up to 6TB (no HDD included); USB Interface: 2 ports(1 Rear), USB2.0 ; RS485: 1 port, For PTZ Control ; Power Supply: DC12V/2A; Power Consumption: 10W(without HDD) ; Working Environment: -10°C ~ +55°C/10%~90%RH / 86~106kpa	100 € 95 €
68.		16CH Penta-brid 720P Compact 1U DVR DAHUA DHI-XVR4116HS The XVR can auto recognize the signal of front-camera without any setting. It supports up to 16ch of HDCVI/ AHD/TVI/CVBS inputs, and 2ch IP camera each channel up to 5MP; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)720P/960H/D1 /HD1 /BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (100M); Max. User Access: 128 users; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more; USB: 2 USB Ports (2 USB 2.0); RS485 1 Port, for PTZ Control; Internal HDD 1 SATA Ports, up to 6TB (no HDD included); Power Supply: DC12V/2A; Power Consumption: <15W (Without HDD)	125 € 105 €
69.		16CH Penta-brid DVR DAHUA DHI-XVR5116HS The XVR can auto recognize the signal of front-camera without any setting. It supports up to 16ch of HDCVI/ AHD/TVI/CVBS inputs, and 8ch IP camera additionally; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)720P/960H/D1/HD1 /BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (1000M); Max. User Access: 128 users; Support IVS(Tripwire/Intrusion/Abandoned/Missing)and Face Detection; Third-party Support; USB: 1 USB 2.0, 1 USB 3.0; RS485 1 Port, for PTZ Control; Internal HDD 1 SATA Ports, up to 6TB (no HDD included); Power Supply: DC12V/3A; Power Consumption: <15W (Without HDD)	159 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



70.		16CH Penta-brid 1080P Mini 1U DVR DAHUA DHI-XVR7116H The XVR can auto recognize the signal of front-camera without any setting. It supports up to 16ch of HDCVI/ AHD/TVI/CVBS inputs, and 8ch IP camera each channel up to 5MP; The XVR supports 5MP HD resolution (2560 x 1920) IPC input for recording, live viewing; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI ,1 VGA; Compression: H.264+/H.264; Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 1080P(1~15fps)/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Network Interface: 1 RJ-45 Port (1000M); Max. User Access: 128 users; Support IVS(Tripwire/Intrusion/Abandoned/Missing)and Face Detection; Third-party Support; USB: 1 USB 2.0, 1 USB 3.0; RS485 1 Port, for PTZ Control; Internal HDD: 2 SATA Ports, up to 6TB capacity for each disk (no HDD included); Power Supply: DC12V/3A; Power Consumption: <15W (Without HDD)	195 €
71.		16 CH Tribrid 1080P-Lite 1U DVR DAHUA DHI-HCVR5216A-S3 Support HDCVI/CVBS/IP video inputs; HDCVI Camera Input: 16 Channel; IP Camera Input: 16+8 Channel, each channel up to 5MP; Audio In/Out 4 Channel input,1 Channel output; Two-way Talk Reuse audio in(channel 1)/out, RCA; Interface: 1 HDMI ,1 VGA; Recording Resolution: 1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Network Interface: 1 RJ-45 Port (1000M); Alarm input: 16; Relay Output: 3; Internal HDD: 2 SATA Ports, up to 6TB capacity for each disk (no HDD included); USB: 2 USB Ports (1 USB 2.0 , 1 USB 3.0); RS485: 1 Port, for PTZ Control; Interoperability ONVIF 2.4.1, CGI Conformant; Power Supply: DC12V/4A; Power Consumption: <15W (Without HDD); Operating Conditions: -10°C ~ +55°C, 86 ~ 106kpa	199 €
72.		16CH 4MP HDCVI DVR DAHUA DHI-HCVR7216AN-4M HDCVI Camera Input 16 Channel; IP Camera Input: 8 Channel, each channel up to 5MP; Audio In/Out: 1/1; Two-way Talk 1 Channel Input, 1 Channel Output, RCA; Interface: 1 HDMI(up to 3840x2160),1 VGA; Resolution: 4MP,1080P, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Record Rate: Main stream: 4MP(1~15fps) 1080P/720P/960H/D1/HD1/BCIF/CIF/QCIF (1~25/30fps), Sub stream: D1/CIF/QCIF(1~25/30fps); Interoperability ONVIF 2.4.1, CGI Conformant; Max. User Access: 128 users; Internal HDD: 2 SATA Ports, up to 6TB capacity for each disk (no HDD included); USB: 2 USB Ports (1 USB 2.0 , 1 USB 3.0); RS485: 1 Port, for PTZ Control; Support IVS(Tripwire/Intrusion/Abandoned/Missing) and Face Detection; Third-party Support: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek, and more; Power Supply: DC12V/5A; Power Consumption: <15W (Without HDD); Operating Conditions: -10°C ~ +55°C, 86 ~ 106kpa	250 €
73.		24CH Tribrid HDCVI DVR DAHUA HCVR5824S-S2 Video Input: 24 channel, BNC ; Standard: Analog PAL, HDCVI: 1080P/720P HDCVI Camera, IP: All channels support 1080P/720P IP Camera ; Interface: 2 HDMI, 1 VGA, 1 TV ; Audio Input: 16 channel, BNC ; Main Stream: 1080P(1~12/15fps) / 720P / 960H / D1 / HD1 / 2CIF / CIF(1~25/30fps); Ethernet: RJ-45 port (10/100M/1000M); Max. User Access: 128 users ; Internal HDD: 8 SATA ports(8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB (no HDD included); External HDD: 1 eSATA port ; USB Interface: 4 ports (2 Rear), USB2.0 ; RS232: 1 port, For PC communication & Keyboard ; RS485: 1 port RS485 for PTZ control, 1 port RS422 for Keyboard ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Power Supply: AC 100~240 V, 50/60 Hz ; Power Consumption: 40W(Without HDD); Working Environment: -10°C ~+55°C	620 €
74.		32CH Tribrid HDCVI DVR DAHUA HCVR5832S-S2 Video Input: 32 channel, BNC ; Standard: Analog PAL, HDCVI: 1080P/720P HDCVI Camera, IP: All channels support 1080P/720P IP Camera ; Interface: 2 HDMI, 1 VGA, 1 TV ; Audio Input: 16 channel, BNC ; Main Stream: 1080P(1~12/15fps) / 720P / 960H / D1 / HD1 / 2CIF / CIF(1~25/30fps); Ethernet: RJ-45 port (10/100M/1000M); Max. User Access: 128 users ; Internal HDD: 8 SATA ports(8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB (no HDD included); External HDD: 1 eSATA port ; USB Interface: 4 ports (2 Rear), USB2.0 ; RS232: 1 port, For PC communication & Keyboard ; RS485: 1 port RS485 for PTZ control, 1 port RS422 for	680 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

		Keyboard ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Power Supply: AC 100~240 V, 50/60 Hz ; Power Consumption: 40W(Without HDD); Working Environment: -10°C ~+55°C	
МРЕЖНИ ВИДЕО РЕКОРДЕРИ (NVRs)			
75.		4CH Smart 1U Network Video Recorder DAHUA DH-NVR4104 Up to 4 channel with 1080P realtime live view ; IP Camera Input: 4 channel ; Audio: 1channel Input, 1channel Output , RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps) ; ONVIF Version 2.3 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	90-€ 70 €
76.		4CH 4POE Network Video Recorder DAHUA DH-NVR4104-P Up to 4 channel with 1080P realtime live view ; IP Camera Input: 4 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps) ; PoE: 4 ports (IEEE802.3at) ; ONVIF Version 2.3 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	130 €
77.		8CH Smart 1U Network Video Recorder DAHUA DH-NVR4108 Up to 8 channel with 1080P realtime live view ; IP Camera Input: 8 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps) ; ONVIF Version 2.3 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	100-€ 90 €
78.		8CH 4POE Network Video Recorder DAHUA DH-NVR4108P Up to 8 channel with 1080P realtime live view ; IP Camera Input: 8 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps) ; PoE: 4 ports (IEEE802.3at) ; ONVIF Version 2.3 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	140-€ 139 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

79.		8CH 8PoE Network Video Recorder DAHUA DH-NVR4108-8P IP Camera Input: 8 channel ; H.264/MJPEG dual codec decoding ; Two-way Talk: 1ch. Input, 1ch. Output, RCA ; Resolution: 1920×1080, 1280×1024, 1280×720, 1024×768 ; Interface: 1 HDMI, 1 VGA ; Resolution: 5Mp(2560×1920) / 3Mp(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1(704×576/704×480) ; Ethernet: 1 RJ-45 port (10/100Mbps); PoE: 8 ports (IEEE802.3af/at); All channel synchronous realtime playback, GRID interface & smart search ; Max.User Access: 128users ; Smart Phone: iPhone, iPad, Android ; Internal HDD: 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports, USB2.0 ; ONVIF Version 2.4 conformance ; 3D intelligent positioning with Dahua PTZ camera ; Power Supply: DC48V/2A ; Power Consumption: NVR: 12W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa	170 € 167 €
80.		16CH Network Video Recorder DAHUA DH-NVR2116-S2 Supported 16 ch. IP Cameras ; Two-way communication: 1-channel input, 1-channel output, RCA; Interface: 1 HDMI, 1 VGA ; Display Resolution: 1920x1080, 1280x1024, 1280x720, 1024x768; Compression: Smart H.264 +/H.264; Recording Resolution: 6Mp, 5Mp, 4Mp, 3Mp, 1080p, 1.3Mp, 720p ; Recording speed: 80Mbps; Ethernet: 1 RJ-45 port (10/100 Mbps); Onvif 2.4 protocol support ; 3D intelligent positioning with PTZ cameras Dahua; Max. Users: 128 users; Smartphone: iPhone, iPad, Android; Internal Hard Drive: SATA, up to 6 TB(No HDD Included) ; USB: 2 x USB 2.0 ports; Power supply: DC12V/2A; Power Consumption: 15W (without HDD); Work environment: -10 ° C ~ + 55 ° C / 10% ~ 90% RH / 86 ~ 106 kPa	85 € 80 €
81.		16CH Smart 1U Network Video Recorder DAHUA DH-NVR4116 Up to 16 channel with 1080P realtime live view ; IP Camera Input: 16 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps) ; ONVIF Version 2.3 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	107 €
82.		16CH Mini 1U Network Video Recorder DAHUA DH-NVR4116H Up to 16 channel with 1080Prealtime live view ; IP Camera Input: 16 channel ; HDMI / VGA simultaneous video output ; Two-way Talk: 1channel Input, 1channel Output, RCA ; H.264/MJPEG dual codec decoding ; Up to 5Mp resolution preview & playback ; Recording Resolution: 5Mp(2560×1920) / 3Mp(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps); ONVIF Version 2.3 conformance ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Support 1 SATA HDD up to 4TB, 2 USB2.0(No HDD Included) ; Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc. ; Power Supply: DC12V/2A ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Dimension(W×D×H): Mini 1U, 325mm×240mm×45mm	113 €
83.		16CH 4POE Network Video Recorder DAHUA DH-NVR4116P Up to 16 channel with 1080P realtime live view ; IP Camera Input: 16 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100Mbps) ; PoE: 4 ports (IEEE802.3at) ; ONVIF Version 2.3 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 1 SATA port, up to 4TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without	157 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



		HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	
84.		16CH 16PoE Network Video Recorder DAHUA DH-NVR4416-16P Up to 5MP Resolution for Preview and Playback; IP Camera Input: 16 channel ; Two-way Talk: 1 Channel Input, 1 Channel Output, RCA; Display Interface: 1 HDMI, 1 VGA, 1TV(BNC) ; Recording Resolution: 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc.; ONVIF 2.4, CGI Conformant ; Alarm Input: 16 Channel, Low Level Effective, Green Terminal Interface; Relay Output: 4 Channel, NO/NC Programmable; Network Interface: 1 RJ-45 Port (10/100/1000Mbps), Ethernet Port: 1 Independent 1000Mbps Ethernet Port; PoE 16 ports (IEEE802.3at/af); Smart Phone: iPhone, iPad, Android; Internal HDD: 4 SATA III Ports, Up to 6 TB capacity for each HDD (No HDD Included) ; eSATA: 1 eSATA Port; USB: 2 USB Ports (1 USB 2.0 , 1 USB 3.0); RS232: 1 port, For PC communication & Keyboard; RS485: 1 Port, for PTZ Control; Power Supply: AC100V ~ 240V, 50 ~ 60 Hz; Power Consumption: <40W (Without HDD); Working Environment: -10°C~+55°C; Third-party Support	420-€ 370 €
85.		32CH 16POE Network Video Recorder DAHUA DH-NVR4832-16P Up to 5MP Resolution for Preview and Playback; IP Camera Input: 32 channel ; Audio: Two-way Talk: 1 Channel Input, 1 Channel Output, RCA; Display Interface: 1 HDMI, 1 VGA ; Record Rate 200Mbps; Recording Resolution: 5Mp (2560×1920) / 3Mp (2048×1536) / 1080P (1920×1080) / 720P (1280×720) / D1 (704×576/704×480) ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100/1000Mbps) ; PoE: 16 ports (IEEE802.3at); ONVIF 2.4, CGI Conformant ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android; Internal Storage: 8 SATA III Ports, Up to 6 TB capacity for each HDD (no HDD included) ; USB: 3 USB Ports (2 USB 2.0 , 1 USB 3.0) ; Power Supply: AC100V~240V, 50~60Hz; Power Consumption: <40W (Without HDD); Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa; Support Multi-brand network cameras	520-€ 499 €
МРЕЖНИ ВИДЕО РЕКОРДЕРИ (NVRs) СО 4К РЕЗОЛУЦИЈА			
86.		8CH Network Video Recorder DAHUA DHI-NVR4208-4K Up to 8 channel with 1080P realtime live view ; IP Camera Input: 8 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 12Mp, 8Mp, 6Mp, 5Mp, 3Mp, 1080P, 1.3Mp, 720P & etc. ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100/1000Mbps) ; ONVIF Version 2.4 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 2 SATA port, up to 12TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10% ~ 90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	326 €
87.		16CH Network Video Recorder DAHUA DH-NVR4216-4K Up to 16 channel with 1080P realtime live view ; IP Camera Input: 16 channel ; Audio: 1channel Input, 1channel Output, RCA ; Display Interface: 1 HDMI, 1 VGA ; Recording Resolution: 12Mp, 8Mp, 6Mp, 5Mp, 3Mp, 1080P, 1.3Mp, 720P & etc. ; Backup Mode: USB Device/Network/Internal SATA burner ; Ethernet: 1 RJ-45 port (10/100/1000Mbps) ; ONVIF Version 2.4 conformance ; Max. User Access: 128 users ; Smart Phone: iPhone, iPad, Android, Windows Phone ; Internal Storage: HDD 2 SATA port, up to 12TB (no HDD included) ; USB: 2 ports (2 Rear), USB2.0 ; Power Supply: Single, DC48V/1.5A ; Power Consumption: NVR: 10W(without HDD), PoE: Max 25.5W for single port ; Working Environment: -10°C~+55°C / 10%~90%RH / 86~106kpa ; Support Multi-brand network cameras: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videotec, Vivotek and etc.	380 €
HARD DRIVES FOR VIDEO SURVEILLANCE			





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

88.		HDD 1TB SATA 24/7 VIDEO SEAGATE ST1000VM002	54 €
89.		HDD 2TB SATA 24/7 TOSHIBA	73 €
90.		HDD 2TB SATA 24/7 VIDEO SEAGATE	75 €
91.		HDD 4TB SATA 24/7 VIDEO SEAGATE ST4000VM000	143 €
92.		HDD 6TB SATA 24/7 VIDEO SEAGATE	227 €

МОНИТОРИ

93.		Full-HD LCD Monitor 22" DAHUA DHL22-S200 Resolution 1920x1080 ; Backlight: WLED ; Luminance(Standard): 200cd/m ² ; Angle of view 130°/178° (vertical / horizontal); Contrast: 600:1 ; Response Time(Grey Scale): 4ms ; PC Signal: VGA(D-Sub)×1 ; Digital Signal: HDMI×1(1920×1080), downward compatible ; Audio Input x 1 (3.5mm); Audio Output: Speaker; Power Consumption (Standard): 23W ; Power Consumption (Standby): ≤0.5W ; Power Supply: AC100-240V~(+/-10%), 50/60 Hz ; Working Temperature: 0°C~40°C ; Working Humidity: 10%~90%	230 €
94.		HD LCD Monitor 32" DAHUA DHL32-S200 Resolution: 1366×768 ; Backlight: CCFL ; DotPitch: 0.51075(H)×0.51075(V) ; Luminance (Standard): 450cd/m ² ; Contrast: 3000:1 ; Angleofview: 178°/178° ; ResponseTime (GreyScale): 8ms ; Video Input: CVBS(BNC)×2 ; PC Signal: VGA(D-Sub)×1 ; Digital Signal: DVI×1 [1080P (1920×1080), downward compatible], HDMI×1 [1080P (1920×1080), downward compatible] ; LoopOut: CVBS(BNC)×2 ; Power Consumption (Standard): 50W ; Power Consumption (Maximum): 80W ; Power Consumption (Standby): ≤1W ; Power Supply: AC100-240V~(+/-10%),50/60Hz ; Control Mode: RS232 Serial control, allwayloop, infrared remote control ; Enclosure material: Metal ; Working Temperature: 0°C~50°C ; WorkingHumidity: 20%~90%	500-€ 480 €
95.		Full-HD LCD Monitor 46" DAHUA DHL46-S100 Resolution: 1920×1080 ; Backlight: CCFL ; Dot Pitch: 0.53025(H)×0.53025(V) ; Luminance (Standard): 450 cd/m ² ; Contract: 3000:1 ; Angle of view: 178°/178° ; Response Time(Grey Scale): 8ms ; Video Input: CVBS(BNC)×2 ; PC Signal: VGA(D-Sub)×1 ; Digital Signal: DVI×1 [1080P (1920×1080), downward compatible], HDMI×1 [1080P (1920×1080), downward compatible] ; LoopOut: CVBS(BNC)×2 ; Power Consumption (Standard): 150W ; Power Consumption (Maximum): 180W ; Power Consumption (Standby): ≤1W ; Power Supply: AC100-240V~(+/-10%),50/60Hz ; Control Mode: RS232 Serial control, allwayloop, infrared remote control ; Enclosure material: Metal ; Working Temperature: 0°C~50°C ; WorkingHumidity: 20%~90%	970-€ 960 €
96.		Full-HD LCD Monitor 49" DAHUA DHL49-S200 Industrial level DID LCD panel, suitable for extensive 7×24 continuous works; Built-in 3D COMB filter and 3D Noise Reduction; Resolution: 1920×1080 (FHD) ; Backlight: LED; Brightness / Luminance(Standard): 450 cd/m ² ; Contrast: 1100:1;Angle of view:178°/178°(vertical/horizontal); Response time: 5.8ms; Input: standard: CVBS(BNC)×2, VGA(D-Sub)×1, DVI-D×1, HDMI×1, RS232×1, USB×1 , optional: Audio×1, RJ45×1, HDCVI×1, SDI×1, DP×1, support video loop; Output: standard: CVBS(BNC)×2, RS232×1 , optional: Audio×1, DP×1; Brightness smart detection, power-saving; Using Tamper-proof metal housing, no radiation; Consumption (Standard): 60W; Consumption (Standby): ≤1W; Power Supply: AC100~240V(+/-10%),50/60Hz; Work Environment Temperature: 0°C~50°C, Humidity:20%~90%	985-€ 970 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322


97.		Држач за монитор за на маса DHL22/27-DZ (за Monitor metal 22" DAHUA DHL22)	8 €
98.		Држач за монитор за на сид DHLS600 (за Monitor metal 32" DAHUA DHL32)	28€
99.		Држач за монитор за на сид DHLBG (за Monitor metal 46" DAHUA DHL46)	28€
100.		Држач за монитор за на сид (за Monitor metal 49" DAHUA DHL49)	28 €

ПРЕНОСНИ ТЕРМИНАЛИ

101.		HD Mobile Portable Terminal MPT300 Main Processor: 1.2G dual core CPU; Operating System: Android 4.1; Focal Length: 3.85mm; Wide-angle: 72.9°±2°; Video: Compression: H.264; Record Resolution: 1080P:25fps; 720P/D1/VGA/CIF/QVGA:30fps; Snapshot: Support; Max. resolution:3264*2448; Audio: Compression: G.711a; Two-way talk: 1.5W loudspeakers, support PTT; LCD: Dimension: 4.0 inch TFT LCD, support touch screen; Resolution: 854*480; Brightness: Automatic control; Battery: Capacity: 4000mA/H; Charging Time: 4~6h; Network: Wireless Access: Bluetooth, Wi-Fi, WCDMA, 4G FDD-LTE, (optional); Positioning system:GPS; Storage: Flash: 16G/32G(optional); SD Card: Support SD1.0; SD1.1; SD2.0 standard, up to 64GB; TF Card: Support TF card to expand storage; Dimension(W×D×H):151 mm× 73 mm× 29.5mm; Weight: 340g; Ingress Protection: IP67; Working Environment: -10°C ~+50°C / 10%~90%RH.	750 €
------	--	--	-------

КОНТРОЛА НА ПРИСТАП

102.		Standalone controller DAHUA DHI-ASI1201A-D Read Format: 125KHz (Proximity); System: Main Processor: 32 Bit; Memory:16M. Input: Door sensor x 1, Exit button x 1, Alarm input x 2; Output: Relay x 3 (Door lock, Bell, Alarm); Reader: Reader x 1; Read Range: 3-8cm (max.).Capacity: Cardholders / Events: 30,000 /150,000. Function: ID Setting: Using friendly CMS or command by keypad; User Management: General, VIP, Guest,Patrol, Black list, Force; Alarm Function: Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm; Schedule Setting: Support 128 groups of schedule, 128 groups of period and 128 groups of holiday period; Interface: To PC: RJ45(10/100M)/RS485; To Reader: Wiegand/ RS485. General: RTC: Yes; Beep Tone: Buzzer; LCD Display: Sensitive touchkeypad with blue backlight; Ingress protection:IP55; Power Supply: 9-15DC/130Ma; Working Environment:-30°C~+60°C; Working Humidity: 95%	69 €
103.		Standalone controller DAHUA DHI-ASI1201A System: Main Processor: 32 Bit; Memory:16M. Input: Door sensor x 1, Exit button x 1, Alarm input x 2; Output: Relay x 3 (Door lock, Bell, Alarm); Reader: Reader x 1; Read Format: 13.56MHz (Mifare); Read Range: 3-8cm (max.).Capacity: Cardholders/Events: 30,000 /150,000. Function: ID Setting: Using friendly CMS or command by keypad; User Management: General, VIP, Guest,Patrol, Black list, Force; Alarm Function: Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm; Schedule Setting: Support 128 groups of schedule, 128 groups of period and 128 groups of holiday period; Interface: To PC: RJ45(10/100M)/RS485; To Reader: Wiegand/ RS485. General: RTC: Yes; Beep Tone: Buzzer; LCD Display: Sensitive touchkeypad with blue backlight; Ingress protection:IP55; Power Supply: 9-15DC/130Ma; Working Environment:-30°C~+60°C; Working Humidity: 95%	71 €
104.		Reader DAHUA DHI-ASR1100A System: Main Processor: 8 Bit; Read Format: 13.56MHz(Mifare) ; Read Range: 6-8cm (max.); Response time: <0.1s; Function: Tamper Alarm: Yes; Interface: To Controller:RS485; General: LCD Display: Blue backlight; Beep Tone: Buzzer; Ingress protection:IP55; Power Supply:9-15VDC/100mA; Working Environment: -30°C~+60°C;Working Humidity: ≤95%	31 €
105.		Reader DAHUA DHI-ASR1101M-D Read Format: 125KHz (Proximity); Support card, password; Read Range: 3-5cm (max.); Response time: <0.1s; Tamper alarm and vandal-proof; Keypad: 12Key(0-9,*,#), number key 5 is a braille button; All-metal buttons with blue backlight; Beep Tone: Buzzer; Surface mounted installation; Ingress protection: IK08, IP55; Power Supply: 9-15VDC/100mA; Working Environment: -30°C ~ +60°C; Working Humidity: ≤95%	40 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440


Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

106.		Standalone Waterproof Fingerprint Reader DAHUA DHI-ASI1212D Wiegand or RS-485 Interface to Reader; Supports Card, Password, Fingerprint and a Combination of Credentials; Format: 13.56 MHz MIFARE; Range: 3 cm to 8 cm; Capacity: Card Holders: 30.000, Events: 150.000, Fingerprints: 3.000; TCP/IP to PC, Support for WAN Communication; Touch Keyboard and LCD display; Add Devices in SmartPSS via P2P Connection; Door Time Out, Intrusion, Duress and Tamper Alarms; Anti-passback and Multi-card Open Options; Supports 128 Efficient Time and Holiday Schedules; Interface: To PC: RJ45 (10/100 Mbps), To Reader: Wiegand 34/26, RS485	HOBO!!! 115 €
107.		Standalone Fingerprint DAHUA DHI-ASI1212A System: Main Processor: 32 Bit; Memory: 16M. Input: Door sensor x 1, Exit button x 1, Alarm input x 1; Output: Relay x 4 (Door lock, Bell, Alarm X 2); Reader x 1; Read Format: 13.56MHz(Mifare); Read Range: 3-8cm (max.); Response Time: <0.1s; Fingerprint Read: Response Time: ≤0.5s; Recognition Time: ≤1.5s; FAR: ≤0.00004%; FRR: ≤0.15%; Capacity: Cardholders /Events: 30,000/150,000. Function: ID Setting: Using friendly CMS by keypad; User Management: General, VIP, Guest, Patrol, Black list, Force; Alarm Function: Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm; Schedule Setting: Support 128 groups of schedule, 128 groups of period and 128 groups of holiday period; Interface: To PC: RJ45 (10/100M) /RS485; To Reader: Wiegand/ RS485. General: RTC: Yes; VoicePrompt: Yes; Beep Tone: Buzzer; LCD Display: Sensitive touch keypad with blue backlight; Ingress protection: IP55; Power Supply: 9-15DC/200mA; Working Environment: -30°C ~+60°C; Working Humidity: ≤95%	150 €
108.		Four Door Access Controller DAHUA ASC1204C Main Processor: 32 bit; Support card, password, fingerprint and combination; Anti-pass back, multi-door interlock, multi-card open; Memory: 16M(32M External); Input ports: door sensor x 4, exit button x 4, alarm x 1; Output ports: door lock x 4, alarm x 1; Reader: Reader x 4; Capacity: Cardholders/Events: 100,000/150,000; User Management: General, VIP, Guest, Patrol, Black list, Force; Alarm Function: Door time out alarm, Intrusion alarm, Duress alarm, Tamper alarm; Schedule Setting: Support 128 groups of schedule, 128 groups of period and 128 groups of holiday period; Interface to PC: RJ45(10/100M)/RS485; Interface to reader: Wiegand/ RS485; RTC: YES; Power Supply: 9-15DC/500mA(6W); Working Environment: -30°C~+60°C; Dimension(W× D× H): 280*320*114mm.	230 €
109.		Card Issuer DAHUA ASM 100 Read Format: 13.56MHz (Mifare); Communication: USB; Power: USB port; Working Current: Working Current<150Ma; Issue Distance: 3cm~8cm; Working Temperature: -30°C ~ +60°C; Working Humidity: 10% ~ 90%; Dimension: 105mm*75mm*20mm; Weight 0.18kg; Issue Warning: When card is successfully issued, there will be LED indicator and beeper sound.	43 €
110.		Card Reader/Writer DAHUA ASM200 Read Format: 13.56MHz (Mifare); Read Distance: >3cm ; Communication: USB; Beep Tone: Buzzer ; Power Supply: 5VDC/100Ma; Working Environment: -30°C~+60°C; Working Humidity: ≤95%; Hotel lock management software licensing forever	80 €
111.		Programmer DAHUA ASH100 Easy to install lock information; Support RF57 card and RF50 card (T5557 card, M1 card); Read Lock Information function, convenient for system diagnosis and inspection; Convenient and accurate time correction function; Easy to output Unlocking Records; Convenient Check-out operation, improving your hotel management system; Use advanced microwave communication technology to realize data exchange between PDA and lock; Humanity operation interface, various functions and easy operation make your hotel management more efficient; Management system supports multi- encoders through net; Usage voltage: 3.0V, (2 AA batteries)	149 €





WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

112.		Hotel lock DAHUA ASL413S Card Technology: Mifare1 card (IC card); Working voltage: DC6V, alkaline battery (4 pcs); Power Consumption: Static<20uA, Dynamic<200uA ; Working Environment: -30~+60°C, 10%~80% RH ; Lock case: SUS304 Stainless steel ; Door thickness: 38mm ~70mm ; Mechanical Key: Support	130 €
113.		Home smart lock DAHUA DHI-ASL6101R Card Type: Mifare 1; Card Features: Contactless, high security, all-in-one possible; Sensor Distance: < 20mm; Sensor Time < 0.5s; Storage Capacity: 50; Password: Keyboard Type: All-touch keyboard; Password Length: 6-12 bits; Storage Capacity: 50; Special Function: Privacy Password: Preventing password to be seen by others. Unlock password (consecutive) mixed with random numbers. Eg: xxx+password+xxx, xxx means random numbers. Passage Mode: Getting in or out freely without any passwords or cards; Non-disturbance Mode: Only administrator password can unlock; Auto Lock: Invalid card swiping for five consecutive times/Invalid password input for three consecutive times will cause system to be locked for three minutes. Battery: Working Voltage: DC4.5V ~ 6.5V, 4 1.5V"AA"battery; Battery Life: About 1 year (10 units/D); Low Battery Warning: < DC4.5V; Emergency Power Supply: 9V battery; Display: Low Voltage: Support; Door Status: False lock status, lock status, passage mode, non-disturbance mode. Structure: Lock Body: American standard; Door Thickness: 40-55mm (customizable); Position Dimension: Door margin 62mm, central distance 97mm; Product Standard: GA374-2001(e-lock); Material: Zinc alloy. General: Working Temperature: -30~+70°C; Relative Humidity: 10%~93%; Salt spray test: ≥200h; Lock case test: ≥100000 times	270 €
114.		Mifare Card IC-M1	0.8 €
115.		Mifare tag	1 €
ВИДЕОДОМОФОНИЈА			
116.		4.3 Inch Analogue Kit DAHUA VTKA-VTO5000C-VTH1200CS 4.3" color TFT LCD display; Cat 5e system, easy installation Monitor VTH1200CS Video Display 4.3" color LCD, resolution: 480x272; Audio Input: 1-ch microphone input (Omni-directional electrets), 1-ch handset pickup input; Audio Output: 1-ch loudspeaker output, 1-ch handset speaker output; Bidirectional Talk: 1-ch bidirectional talk, two way; Net Interface: RJ45 (non-Ethernet) plug connected with distributor, including power supply, AV and control signal; RS485: Bus control and software upgrading; DC Power: 24V; Working Temperature: -5°C – +55°C Outdoor unit VTO5000C Resolution: 600 lines; Support Night vision; Audio Input: 1-ch microphone input, Audio Output: 1-ch loudspeaker output, Bidirectional Talk: 1-ch bidirectional talk, two way; Power DC: 24V; Power Consumption: Standby ≤1W, work≤4W; Working Temperature: -20°C~+60°C	69 €
117.		7 Inch Analogue Kit DAHUA VTKB-VTO5110B-VTH1500B 7" color TFT LCD display; Cat 5e system, easy installation; Support monitoring, video talk, unlock function; Weather -proof outdoor unit (IP65); Color CMOS camera; Support night vision Monitor VTH1500B Video Display 7" color LCD, resolution: 800x480; Audio Input: 1-ch microphone input (Omni-directional electrets), Audio Output: 1-ch loudspeaker output, Bidirectional Talk: 1-ch bidirectional talk, two way; Net Interface: RJ45 (non-Ethernet) plug connected with distributor, including power supply, AV and control signal; RS485: Bus control and software upgrading; DC Power: 24V; Working Temperature: -5°C – +55°C Outdoor unit VTO5110B Resolution: 600 lines; Support Night vision; Audio Input: 1-ch microphone input, Audio	99 €

Satel
Intelligent Security Solutions

DAHUA
TECHNOLOGY



PLANET
Networking & Communication

JVC

BENINCA
TECHNOLOGY TO OPEN

Inova-bg Ltd
SECURITY SYSTEMS

VACRON
ADVANCES IN SECURITY SOLUTIONS

ZHUDELE

Security Vision Systems
MOBOTIX

cofem, s.a.
1973

ACTi
Connecting Vision

SAMSUNG

BOSCH

Surveon



WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 403000534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

		Output: 1-ch loudspeaker output, Bidirectional Talk: 1-ch bidirectional talk, two way; Power DC: 24V; Power Consumption: Standby ≤1W, work≤4W; Working Temperature: -20°C~+60°C	
118.		Wi-Fi Color Indoor Monitor DAHUA DHI-VTH5221DW IPC surveillance; Video Compression: H.264; Audio Input: All-direction Microphone; Audio Output: Built-in Loudspeaker; Bidirectional Talk: Support Dual-way Bidirectional talk; LCD Screen: 7" 1024x600, Capacitive; Alarm In: 6; Alarm Out: 1; RS485: 1; Network Protocol: TCP/IP; Wi-Fi: IEEE802.11b/g/n; Ethernet: 10M/100Mbps Self-adaptive; Memory Slot: Micro SD, Max 32G; Record and snapshot (SD card needed); Power: DC 12V, PoE(802.3af); Power Consumption: Standby ≤1W, Work≤8W; Working Temperature: -10°C~+55°C; Relative Humidity: 10% ~ 90%RH	120 €
119.		1MP Wi-Fi Villa Outdoor Station DAHUA DHI-VTO2111D-WP Image Sensor: 1/4" 1MP CMOS; Lens: 2.2mm, Angle of View: D:125° H:105°; Day/Night: ICR; Audio Input: Omnidirectional Mic; Audio Output: Built-in Speaker; Bidirectional Talk: Support Dual-way Bidirectional talk; Keypad: Single Mechanical Button; Reader: Mifare Card; Body Approaching: 1m; Door Control: 2(1 relay out for main lock, 1 extended by access control module); Alarm In: 2(1ch unlock button, 1ch feedback); RS485: 1; Wi-Fi: IEEE802.11b/g/n; Ethernet: 10M/100Mbps Self-adaptive; Network Protocol: TCP/IP; Ingress Protection: IP65; Tamper Switch: 1; Memory Slot: Micro SD, Max 64G; Power: DC 12V, PoE(802.3af); Power Consumption: Standby ≤1W, Work ≤7W; Working Environments: - 30°C~+60°C; Relative Humidity: 10%~90%RH	76 €
120.		Video doorphone 7-inch Color Indoor Monitor DAHUA DH-VTH1560B-W + power supply 0160B12V1AG-A0(1075) Монитор + напојување System: Main Processor: Built-in microcontroller; Operation systems: Embedded LINUX operating system. Video: Compression: H.264; Resolutions: 800*480; Audio: Audio input: All-direction microphone; Audio Output: Embedded loudspeaker; Bidirectional talk: Support bidirectional talk; Operation modes: Input: Mechanical keys (emergency, protection, video talk, monitoring, unlock), Touch screen technology. Alarm: Alarm input: Support 8 channels input; Network: Ethernet: 10M/100Mbps adaptive; Network protocol: TCP/IP; Power: DC 10~15V or supply directly by Special switching power; Power Consumption: Standby ≤1.5W, work≤7W. General: Work environment: Temperature: -10°C~+60°C; Humidity: 10~90%RH ;	130 €
121.		Villa outdoor station DAHUA DH-VTO2000A +housing DH-VTOB108 + power supply 0160B12V1AG-A0(1075) Позивна единица за монитор (DH-VTH1560B-W) + кукиште за позивната единица(DH-VTOB108) + напојување System: Main processor: Embedded micro processor; Operation system: Embedded LINUX OS; Video Compression Standard: H.264. Video: Input/Approaching Induction: 1.3MP CMOS HD camera; Night Vision: Support; Audio: Audio Output: Build-in speaker; Audio Input: Omnidirectional Mic; Bidirectional Talk: Support dual-way bidirectional talk. Operation: Input: Single key input; Mode: Door Lock Status Check: Support (optional); Network: Ethernet: 10M/100Mbps Self-adaptive; Network Protocol: TCP/IP. General: Working Environments: -30 °C~+70°C; Relative Humidity: 10%~90%RH	153 €

Цените се дадени во евра без вкalkулиран ДДВ 18% и за мониторите 5% ДДВ.

ДТУ Визард Системи ДООЕЛ го задржува правото на промена на цените без претходна најава.

