



WIZARD SYSTEMS®

За свет во кој зборот грижа не постои

ДТУ Визард Системи ДООЕЛ Скопје, Ул. Црноризец Храбар бр. 32 Скопје

| Тел: +389 2 246 9999 | + 389 2 2402999

| ДБ.МК 4030005534810 |

Комерцијална Банка | Ж.С-ка.: 300000002030440

Прокредит Банка | Ж.С-ка.: 380728142500174

Web: www.wizard.com.mk | E-mail: contact@wizard.com.mk



EN ISO 9001
20 100 141364321
EN ISO 14001
20 104 141364322

PRICE LIST

01.06.2017

No.		Specification	Unit price
АНАЛОГНИ КАМЕРИ			
1.		Varifocal IR Bullet Camera HIKVISION DS-2CE15A2P-VFIR3 Image Sensor: 1/3" DIS ; Effective Pixels: 976 (H) × 496 (V); Min. Illumination: 0.1 Lux @ (F1.2,AGC ON), 0 Lux with IR ; Lens: 2.8-12mm @ F1.4 ; Angle of view: 80° - 27.2° ; Angle Adjustment: Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360° ; Day & Night: IR cut filter with auto switch ; Horizontal Resolution: 700 TVL ; Video Output: 1Vp-p composite output (75 Ω/BNC) ; IR Range: Approx. 30 to 40 meters ; S/N Ratio: More than 62 dB ; Working Temperature/ Humidity: -40 °C ~ 60 °C, Humidity 90% or less (non-condensing) ; Power Supply: 12 V DC ± 10% ; Power Consumption: Max. 4 W (Max. 5 W with IR cut filter on) ; Ingress protection level: IP66 ; With bracket	52€
TURBO HD КАМЕРИ			
2.		1080P TURBO HD IR TURRET CAMERA HIKVISION DS-2CE56D1T-IRM Image Sensor: 2 MP CMOS Image Sensor; Effective Pixels :1930(H)*1088(V); Min. Illumination: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR; Shutter Time: 1 / 25(1 / 30) s to 1 / 50,000 s; Lens: 2.8mm , Lens Mount: M12; Angle Adjustment: Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°; Day & Night: ICR ; OSD menu controlled via UTC; Synchronization: Internal synchronization; Video Frame Rate: 1080p@25fps / 1080p@30fps; HD Video Output: 1 Analog HD output, HD1080P Video Output ; S / N Ratio: More than 52dB; BLC: Support; Working Temperature / Humidity: -40°C - 60°C, Humidity 90% or less (non-condensing); Power Supply: 12 VDC; Power Consumption: Max. 3W; Weather Proof Ratings: IP66; IR Range: Up to 20m ; Communication: Up the coax Protocol: HIKVISION-C(Coaxitron)	36€
3.		1080P TURBO HD EXIR TURRET CAMERA HIKVISION DS-2CE56D1T-IT3 Image Sensor: 2 MP CMOS Image Sensor; Effective Pixels: 1930(H)*1088(V); Min. Illumination: 0.01 Lux @(F1.2,AGC ON), 0 Lux with IR Shutter speed 1/25(1/30) s to 1/50,000 s; Lens 3.6mm ; Angle of View: 84.3° ; Angle Adjustment Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°; Day & Night: ICR; Synchronization: Internal synchronization; Video Frame Rate: 1080p@25fps/1080p@30fps HD; Video Output: 1 Analog HD output, HD1080P Video Output ; S / N Ratio: More than 52dB; BLC: Support; Working Temperature / Humidity: -40°C – 60°C, Humidity 90% or less (non-condensing); Power Supply: 12 VDC; Power Consumption: Max. 3.5W; IR Range: Up to 40m, EXIR technology; IP66 weatherproof; OSD menu controlled via UTC ; Communication: Up the coax Protocol: HIKVISION-C(Coaxitron)	45€
4.		1080P TURBO HD VARIFOCAL TURRET CAMERA HIKVISION DS-2CE56D1T-VFIR3 Image Sensor: 2MP CMOS Image Sensor; Effective Pixels:1930(H)*1088(V); Min. illumination: 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR; Shutter Time: 1/25(1/30)s to 1/50,000s; Lens: 2.8 - 12 mm @ F1.4 ; Angle of view: 114.5°- 35.1°; Day & Night: ICR ; Angle Adjustment: Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°; Synchronization: Internal synchronization; Video Frame Rate: 1080p@25fps/1080p@30fps HD; Video Output: 1 Analog HD output, up to 1080P resolution ; S/N Ratio: >62dB; White Balance: Auto/User/Push/8000K/6000K/4200K/3000K; Privacy Mask: On/Off, maximum 2 zones; Motion Detection: On/Off, maximum 4 zones; BLC: Support ; Operating Conditions: -40°C – 60°C , Humidity 90% or less (non-condensing); Power Supply:12 VDC±15%; Power Consumption: Max. 4.5W; Protection Level: IP66; IR Range: Up to 40m; OSD menu	66€
5.		1080P TURBO HD BULLET CAMERA HIKVISION DS-2CE16D1T-IR Image Sensor: 1 / 2.7" Progressive Scan CMOS; Effective Pixels: 1930(H)*1088(V); Min. Illumination: 0.1 Lux @ (F1.2,AGC ON),0 Lux with IR; Shutter Time: 1 / 25(1 / 30) s to 1 / 50,000 s; Lens: 3.6mm ; Angle of View: 90°; Day & Night: ICR ; Angle Adjustment: Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°; Synchronization: Internal synchronization; Video Frame Rate: 1080p@25fps / 1080p@30fps HD; Video Output: 1 Analog HD output, HD1080P Video Output; S / N Ratio: More than 52dB; White Balance: Auto/ User / Push/ 8000K/ 6000K/ 4200K/ 3000K; Privacy Mask: On / Off, maximum 2 zones; OSD menu controlled via UTC ; Motion Detection: On / Off, maximum 4 zones; BLC: Support; Weather Proof Ratings: IP66; IR Range: Up to 20m ; Communication: Up the coax Protocol: HIKVISION-C(Coaxitron); Working Temperature / Humidity: -40°C - 60°C, Humidity 90% or less (non-condensing); Power Supply: 12 VDC; Power Consumption: Max. 3W ; With bracket	36€
6.		1080P TURBO HD EXIR BULLET CAMERA HIKVISION DS-2CE16D1T-IT3 Image Sensor: 2 Megapixel high-performance CMOS; Effective Pixels: 1930(H)*1088(V); Min. Illumination: 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR; Shutter	45€

		Time: 1/25(1/30) s to 1/50,000 s; Lens: 3.6mm ; Angle of View: 84.3°; Day & Night: ICR ; Synchronization: Internal synchronization; Video Frame Rate: 1080p@25fps / 1080p@30fps HD ; Video Output: 1 turbo HD output; S/N Ratio: More than 52dB; BLC:Support; Working Temperature: -40°C – 60°C, Humidity 90% or less (non-condensing); Power Supply: 12V DC; Power Consumption: Max. 3.5W; Weather Proof Ratings: IP66 ; IR Range:EXIR technology, up to 40m IR distance ; Communication: Up the coax Protocol: HIKVISION-C(Coaxitron); OSD menu controlled via UTC ; With bracket	
7.		1080P TURBO HD VF BULLET CAMERA HIKVISION DS-2CE16D1T-AVFIR3 Image Sensor: 2 MP CMOS Image Sensor ; Effective Pixels:1930(H)*1088(V); Min. Illumination: 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR Shutter speed 1/25(1/30) s to 1/50,000 s; Lens: 2.8-12mm , @ F1.4 ;Angle of view: 105.2° - 32.8°; Lens Mount: φ14; Day & Night: ICR ; Synchronization: Internal synchronization; Video Frame Rate: 1080p@25fps/1080p@30fps HD; Video Output: 1 Analog HD output, HD1080P Video Output ; S / N Ratio: More than 52dB; BLC: Support ; OSD menu controlled via UTC;Working Temperature / Humidity: -40°C - 60°C, Humidity 90% or less (non-condensing); Power Supply: 12 VDC, -A: 12 VDC, 24 VAC; Power Consumption: Max. 6W; Weather Proof Ratings: IP66 ; IR Range: Up to 40m ; Communication: Up the coax Protocol: HIKVISION-C(Coaxitron); With bracket	75€
8.		1080P TURBO HD BOX CAMERA HIKVISION DS-2CC12D9T Image Sensor: 2MP CMOS Image Sensor ; Effective Pixels: 1944(H)*1092(V); Min. illumination: 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR; 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR; Shutter Time: 1/25(1/30)s to 1/50,000s; Day & Night:ICR; Synchronization: Internal synchronization; WDR: 120dB; Video Frame Rate: 1080p@25fps/1080p@30fps; HD Video Output: 1 Analog HD output ; CVBS Output: 1Vp-p Composite Output(75Ω/BNC): S/N Ratio: > 62dB; Privacy Mask: On/Off, maximum 8 zones; Motion Detection: On/Off, maximum 4 zones; BLC: Support; Operating Conditions: -30°C - 60°C, Humidity 90% or less (non-condensing); Power Supply: 12 VDC±15%, -A: 24V±15% AC, 12V±15% DC; Power Consumption: Max. 4W, -A: Max. 6W Communication Up the coax, Protocol: HIKVISION-C(TVI output); Without lens and bracket	85€
IP МЕГАПИКСЕЛНИ КАМЕРИ			
9.		1.3MP Fixed Dome Network Camera HIKVISION DS-2CD2112F-I Image Sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: 0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR, 0.028 Lux @ (F2.0, AGC ON) ,0 Lux with IR ; Shutter time: 1/3 s to 1/100,000 s ; Lens: 2.8mm@ F2.0, Angle of view: 92.5° ; Adjustment Range: Pan:0° - 355°, Tilt: 0° - 75°, Rotation: 0-355°; Day& Night: IR cut filter with auto switch ; 3D DNR & DWDR & BLC ; Max. Image Resolution: 1280x960 ; Network Storage: Built-in Micro SD/SDHC/SDXC slot, up to 128G , NAS(NFS, SMB/CIFS); System Compatibility: ONVIF (Profile S, Profile G), PSIA, CGI, ISAP ; Communication Interface: RJ45 10M / 100M Ethernet interface ; Impact Protection: IK10, Weather Proof: IP66 ; IR Range: Up to 30m ; Operating Conditions: -30 °C ~ 60 °C, Humidity 95% or less (non-condensing); Power Supply: 12 VDC ± 10%, PoE (802.3af)	69€
10.		1.3MP IR Bullet Network Camera HIKVISION DS-2CD2012F-I Image Sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: 0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR ; Shutter time: 1/3 s to 1/100,000 s ; Lens: 4mm@ F2.0 , Angle of view: 73.1° ; Day& Night: IR cut filter with auto switch ; 3D DNR & DWDR & BLC ; Network Storage: Built-in Micro SD/SDHC/SDXC slot, up to 128G , NAS(NFS, SMB/CIFS); System Compatibility: ONVIF , PSIA, CGI, ISAPI ; Communication Interface: 1 RJ45 10M / 100M Ethernet interface ; Weather Proof: IP66 ; IR Range: Up to 30m ; Operating Conditions: -30 °C ~ 60 °C, Humidity 95% or less (non-condensing); Power Supply: 12 VDC ± 10%, PoE (802.3af); With bracket	69€
11.		1.3MP WI-FI IR CUBE NETWORK CAMERA HIKVISION DS-2CD2412F-IW Image Sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: 0.01 lux @F1.2, AGC ON, 0 lux with IR ; Shutter time: 1/25s ~ 1/100,000s; Lens: 4mm@ F2.0, Angle of view: 73.1°(4mm) ; Day & Night: IR cut filter with auto switch ; IR Range: 10 meters ; PIR: Angle of detection: 80°, Detection range: 10m ; DWDR/3D DNR/BLC ; Video Compression: H.264 / M-JPEG ; Max. Image Resolution: 1280 × 960 ; System Compatibility: ONVIF , PSIA, CGI, ISAPI ; Communication Interface: 1 RJ45 10 M / 100 M Ethernet interface ; On-board storage: Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB ; Operating Conditions: -30°C ~ 60°C, Humidity 95% or less (non-condensing) ; Power supply: DC12V±10% / PoE (802.3af) ; With bracket	85€
12.		2MP IPC MINI DOME HIKVISION DS-2CD2E20F Image Sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: 0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR ; Shutter Speed: 1/3 s to 1/100,000 s ; Lens: 4mm ; Angle of view: 85° ; Day&Night: IR cut filter with auto switch ; 3D DNR,WDR ; Angle Adjustment Pan:0° - 355°, Tilt: 0° - 80° ; Up to 2 megapixel (1920 × 1080) resolution ; Video Compression: H.264/ MJPEG ; Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB ; Standard: ONVIF , PSIA, CGI, ISAPI; Communication Interface: 1 RJ45 10M/100M Ethernet interface; Operating Conditions: -10°C – 40°C, Humidity 95% or less (non-condensing) ; Power Supply: 12 V DC ± 10% PoE (802.3af) □ □ □	94€
13.		3MP IR CUBE NETWORK CAMERA HIKVISION DS-2CD2432F-I Image Sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: 0.07Lux @ (F1.2, AGC ON) ,0 Lux with IR ; Shutter time: 1/25(1/30) s to 1/100,000 s ; Lens: 2.8mm@ F2.0 ; Day & Night: IR cut filter with auto switch ; IR Range: 10 meters ; PIR: Angle of detection: 80°, Detection range: 10m ; DWDR/3D DNR/BLC ; Video Compression: H.264 / M-JPEG ; Max. Image Resolution: 2048×1536 ; Full HD1080p Video ; System Compatibility: ONVIF , PSIA, CGI, ISAPI ; Audio: Internal Microphone and Speaker ;	99€

		Communication Interface: 1 RJ45 10M / 100M ethernet interface ; On-board storage: Built-in Micro SD/SDHC/SDXC slot, up to 64 GB ; Operating Conditions: -30°C ~ 60°C, Humidity 95% or less (non-condensing) ; Power Supply: 12 VDC ± 10%, PoE (802.3af) ; With bracket	
14.		3MP VF IR Dome Network Camera HIKVISION DS-2CD2732F-I Image sensor: 1/3" progressive scan CMOS ; 3 megapixel (2048 x 1536) high resolution ; Min. illumination: 0.07 lux@F1.2, AGC on, 0.1 lux@F1.4, AGC on, 0 lux with IR ; Shutter time: 1/25s (1/30s) ~ 1/100,000s ; Lens: 2.8 ~ 12mm @ F1.4 , Angle of view: 98° ~ 30.5° ; Angle adjustment: Pan: 0° ~ 355°, tilt: 0° ~ 75°, rotation: 0° ~ 355° ; IR range: Up to 20m ; Day & night: ICR ; Digital noise reduction: 3D DNR ; Wide dynamic range: Digital WDR ; Backlight compensation: Yes, zone configurable ; System compatibility: ONVIF , PSIA, CGI ; Communication interface: 1 RJ45 10M / 100M Ethernet port ; On-board storage: Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB ; Power supply: DC12V ± 10%, PoE (802.3af) ; Power consumption: Max. 5.5W ; Ingress protection level: IP66 ; Operating conditions: -30°C ~ 60°C , humidity 95% or less (non-condensing)	135€
15.		3MP MINI DOME NETWORK CAMERA HIKVISION DS-2CD2532F-I Image sensor: 1/3" progressive scan CMOS ; Min. illumination: 0.19lux @ F2.0, AGC on, 0 lux with IR ; Shutter time: 1/30s ~ 1/100,000s ; Lens: 4mm@F2.0, angle of view: 75.8° ; Day & night: ICR ; DWDR & 3D DNR & BLC ; Up to 3 megapixel (2048 x 1536) resolution ; Full HD1080p real-time video ; IR LEDs (up to 10m) ; Protocols: TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos ; System compatibility: ONVIF , PSIA, CGI ; Communication interface: 1 RJ45 10M / 100M ethernet port ; On-board storage: Built-in Micro SD card slot, up to 64 GB ; Operating conditions:-30 °C ~ 60 °C, humidity 95% or less (non-condensing) ; Power supply: DC12V ± 10%, PoE (802.3af) ; Power consumption: Max. 7W ; Ingress protection level: IP66	140€
16.		1.3MP WDR Pinhole Network Camera HIKVISION DS-2CD6412FWD-10 Image sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: Color: 0.037 Lux @(F2.3,AGC ON); B/W: 0.0037Lux @(F2.3,AGC ON); Shutter Speed: 1s ~ 1/100,000s; IR cut filter with auto switch; Lens: 3.7mm@ F2.3, angle of view: 57° ; True WDR, up to 120dB; Built-in Micro SD/SDHC/SDXC card slot, up to 128GB ; Support HLC, Defog and EIS; Standard: ONVIF (PROFILE S, PEOFILE G), PSIA, CGI, ISAPI; Communication: 1 RJ45 10M/100M Ethernet interface/ 1 RS232/ 1 RS-485; Audio Interface: 1 3.5mm audio output interface; 1 built-in speaker by default, support echo cancellation; Power Supply: 12 VDC ± 10% / PoE (802.3af)	235€
17.		3MP EXIR Camera with POE POWER HIKVISION DS-2CD3232-I5 Image Sensor: 1/3" Progressive Scan CMOS ; Can output Full HD 1080pReal-time image ; Min. Illumination: 0.01 lux @ F1.2, AGC ON, 0 lux with IR 0.028 lux @ F2.0, AGC ON, 0 lux with IR ; Shutter time: 1/25s ~ 1/100,000s ; Lens: 4mm @ F2.0, Angle of view: 22° ; Day& Night: IR cut filter with auto switch ; Digital noise reduction: 3D DNR ; IR Range: EXIR: 30m to 50m ; Max. Image Resolution: 2048x1536 ; BLC: Yes, zone configurable ; Protocols: TCP/IP,ICMP, HTTP, HTTPS,FTP,DHCP,DNS, DDNS, RTP ,RTSP, RTCP ,PPPoE, NTP, UPnP, SMTP, SNMP,IGMP, 802.1X,QoS,IPv6,Bonjour (SIP, SRTP optional) ; System Compatibility: ONVIF , PSIA, CGI ; Communication Interface: 1 RJ45 10M / 100M ethernet interface ; Operating Conditions: -30 °C ~ 60 °C, Humidity 95% or less (non-condensing) ; Power Supply: 12 VDC ± 10%, PoE ; Power Consumption: max. 7W (Max. 9W with IR cut filter on) ; Weather Proof: IP66 ; without bracket	85€
18.		4MP IR BULLET NETWORK CAMERA HIKVISION DS-2CD2042WD-I Image Sensor:1/3" Progressive Scan CMOS ; Min. Illumination: 0.01Lux @ (F1.2, AGC ON), 0 Lux with IR ; Shutter time: 1/3 s to 1/10,000 s ; Lens: 4mm @ F2.0, Angle of view: 83° ; Day& Night: IR cut filter with auto switch ; Up to 30m IR range ; Wide Dynamic Range: 120 Db ; Digital noise reduction: 3D DNR ; Video Compression: H.264/MJPEG/H.264+ ; Up to 4 megapixel high resolution ; Full HD1080p video ; System Compatibility: ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI ; Communication Interface: 1RJ45 10M / 100M Ethernet interface ; Operating Conditions: -30 °C ~ 60 °C, Humidity 95% or less (non-condensing) ; Power Supply: 12 VDC ± 10%, PoE (802.3af) ; Power Consumption: Max. 5W ; Weather Proof: IP66 ; Support Mobile Monitoring via EZVIZ P2P ; With bracket	98€
19.		3MP Vari-focal IR Bullet Camera HIKVISION DS-2CD2632F-I Image Sensor: 1/3" Progressive Scan CMOS ; Min. Illumination: 0.07Lux @(F1.2,AGC ON), 0 Lux with IR, 0.1Lux @(F1.4,AGC ON), 0 Lux with IR ; Shutter time: 1/3s ~ 1/100,000s ; Lens: 2.8 - 12 mm @ F1.4,Angle of view: 105.2°-31.9° ; Day& Night: IR cut filter with auto switch ; 3D DNR & DWDR & BLC ; Max. Image Resolution: 2048x1536 ; System Compatibility: ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI ; Communication Interface: 1 RJ45 10M / 100M Ethernet interface ; On-board storage: Built-in Micro SD/SDHC/SDXC slot, up to 128 GB ; Weather Proof: IP66 ; IR Range: Up to 30m ; Operating Conditions: -30 °C ~ 60 °C, Humidity 95% or less (non-condensing); Power Supply:12 VDC ± 10%, PoE (802.3af); With bracket	170€
20.		2MP Network IR Speed Dome with POE power HIKVISION DS-2DE4582-A 1/2.8" Progressive Scan CMOS, up to 1920x1080 ; Minimum Illumination: Color: 0.05Lux@ (F1.6, AGC On), B/W: 0.01Lux@(F1.6, AGC On); 0 lux with IR ; White Balance: Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp ; AGC: Auto/Manual ; S/N Ratio: ≥ 52Db ; BLC: ON/OFF ; HLC: Support ; WDR: Support ; Shutter Time: 1/1~ 1/10,000s ; Day& Night: ICR ; Digital Zoom: 16X ; Privacy Masking: 2 privacy masks programmable ; Focal Length: 2.8-12mm, 4X ; Angle of View: 115-33.8 degree (Wide-Tele) ; Pan Range: 360°endless, Tilt Range: -10° ~ 90° (auto fl ip) ; Number of	295€

		Preset: 256 ; Patrol: 8 patrols, up to 32 presets per patrol ; Monitor Output: 1.0Vp-p / 75Ω, NTSC (or PAL) composite, BNC ; Audio Input: 1 Mic in/Line in interface ; Line input: 2-2.4Vp-p ; output impedance: 1KΩ, ±10% ; Ethernet: 10Base -T, /100Base-TX, RJ45 Connector ; Mini SD Card: Manual REC / alarm REC, built-in SD/SDHC slot, up to 32GB ; Application programming: Open-ended API, support ONVIF , PSIA Power Consumption: 24WAC / PoE+ (802.3at), Max 20W ; Protection Level: IP66 standard (outdoor dome)	
21.		NETWORK KEYBOARD HIKVISION DS-1100KI LCD screen: 7" TFT LCD monitor with touch panel ; Joystick: 3-axis joystick ; Up to 256 units of DVR/Network camera/Speed dome management. 1-ch HD 1080p video stream decoding. USB2.0 interface for video backup ; Control mode: IP-based ; Communication interface: 1 RJ45 10M/100M/1000M adaptive Ethernet interface; 1 RS-232 interface; 1 RS-485 interface; 1 USB2.0 interface (for data storage and device upgrade) ; Power supply: 12VDC ; Power consumption: ≤15W ; Working temperature: -10°C ~ +55°C ; Working humidity: 10%~90%	670€
ДИГИТАЛНИ ВИДЕО РЕКОРДЕРИ			
22.		4CH 960H DVR HIKVISION DS-7204HVI-SV H.264 video compression ; Video input: 4-ch, BNC (1.0 Vp-p, 75 Ω) ; HDMI / VGA output: 1ch, resolution: 1080P: 1920×1080/60Hz; SXGA: 1280×1024/60Hz; 720P: 1280×720/60Hz; XGA: 1024×768/60Hz ; CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL:704 × 576 ; Audio input: 1-ch, RCA (2.0 Vp-p, 1 kΩ) ; Audio output: 1-ch, RCA (Linear, 1 kΩ) ; CIF resolution real-time recording ; Up to WD1(960*576) resolution recording ; Encoding resolution: WD1 / 4CIF / 2CIF / CIF / QCIF ; Dual-stream: Support Sub-stream @ CIF / QCIF ; Frame rate: WD1 / 4CIF / 2CIF @ 12 fps, CIF / QCIF @ 25 fps ; HDD capacity Up to 4TB(No HDD Included) ; Network interface: 1, RJ45 10M / 100M Ethernet interface ; Serial interface: 1 RS-485 interface, half-duplex ; USB interface: 2, USB2.0 ; Protocols: NTP, SMTP, NFS, UPnP and iSCSI ; Power supply: 12 VDC;Consumption: ≤ 10 W ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10% ~ 90%	63€
23.		4CH DVR HIKVISION DS-7204HWI-E1/A Analog video input: 4-ch ; IP video input: 1-ch, up to 720P resolution ; Video input interface: BNC (1.0 Vp-p, 75 Ω), PAL /NTSC self-adaptive ; Audio input: 1-ch, RCA (2.0 Vp-p, 1 kΩ), Two-way audio input 1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input) ; HDMI / VGA / CVBS output ; Encoding resolution: WD1 / 4CIF / 2CIF / CIF / QCIF ; Frame rate: 25 fps (P) ; Hard disk: 1 SATA interface up to 4TB capacity (no HDD included); Network interface: 1, RJ45 10M / 100M Ethernet interface ; USB interface: 2, USB 2.0 ; Power supply: 12VDC ; Working temperature: -10°C ~+55°C; Working humidity 10% ~ 90%	57€
24.		8CH DVR 960H HIKVISION DS-7208HWI-SH H.264 video compression ; Video input: 8-ch, BNC (1.0 Vp-p, 75 Ω) ; HDMI / VGA output: 1-ch, resolution: 1080P: 1920×1080×60Hz UXGA: 1600×1200×60Hz SXGA: 1280×1024×60Hz ; 720P: 1280×720×60Hz ; XGA: 1024×768×60Hz ; CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL:704 × 576 ; Audio input: 1-ch, RCA (2.0 Vp-p, 1 kΩ) ; Audio output: 1-ch, RCA (Linear, 1 kΩ) ; Video loop out (optional): 4-ch, BNC (1.0 Vp-p, 75 Ω) ; WD1(960*576) resolution real-time recording ; Encoding resolution: WD1 / 4CIF / 2CIF / CIF / QCIF ; Dual-stream: Support Sub-stream @ CIF / QCIF ; HDD capacity Up to 4TB(No HDD Included) ; Network interface: 1, RJ45 10M / 100M Ethernet interface ; Serial interface: 1 RS-485 interface, half-duplex ; USB interface: 2, USB2.0 ; Protocols: NTP, SMTP, NFS, UPnP and iSCSI ; Power supply: 12 VDC; Consumption: ≤ 10 W ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10% ~ 90%	101€
25.		8CH DVR HIKVISION DS-7108HWI-SH Analog video input: 8-ch ; IP video input: 1-ch, up to 720P resolution ; Video input interface: BNC (1.0 Vp-p, 75 Ω), PAL /NTSC self-adaptive ; Audio input: 1-ch, RCA (2.0 Vp-p, 1 kΩ), Two-way audio input 1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input) ; HDMI / VGA / CVBS output ; Encoding resolution: WD1/4CIF/2CIF/CIF/QCIF ; Frame rate: 25 fps (P) ; Hard disk: 1 SATA interface up to 4TB capacity (no HDD included); Network interface: 1, RJ45 10M / 100M Ethernet interface ; USB interface: 2 × USB 2.0 ; Power supply: 12VDC ; Working temperature: -10 °C ~+55 °C ; Working humidity 10% ~ 90%	65.5€
26.		16CH DVR HIKVISION DS-7116HWI-SH Analog video input: 16-ch ; IP video input: 1-ch, up to 720P resolution ; Video input interface: BNC (1.0 Vp-p, 75 Ω), PAL /NTSC self-adaptive ; Audio input: 1-ch, RCA (2.0 Vp-p, 1 kΩ), Two-way audio input 1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input) ; HDMI / VGA / CVBS output ; Encoding resolution: WD1/4CIF/2CIF/CIF/QCIF ; Frame rate: 25 fps (P) ; Hard disk: 1 SATA interface up to 4TB capacity (no HDD included); Network interface: 1, RJ45 10M / 100M Ethernet interface ; USB interface: 2 × USB 2.0 ; Power supply: 12VDC ; Working temperature: -10 °C ~+55 °C ; Working humidity 10% ~ 90% .	106€
27.		24CH Standalone DVR HIKVISION DS-7324HI-SH H.264 video compression ; Video input: 24-ch, BNC (1.0 Vp-p, 75 Ω) ; HDMI / VGA output: 1ch, resolution: 1080P: 1920×1080/60Hz; SXGA: 1280×1024/60Hz; 720P: 1280×720/60Hz; XGA: 1024×768/60Hz ; CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL:704 × 576 ; Audio input: 4-ch, RCA (2.0 Vp-p, 1 kΩ); Audio output: 2-ch, RCA (Linear, 600 Ω) ; Alarm in: 16 ; Alarm out: 8 ; 2CIF resolution real-time recording ; Encoding resolution: WD1 / 4CIF / 2CIF / CIF / QCIF ; Frame rate: WD1 / 4CIF: 15 fps, 2CIF / CIF / QCIF: 25 fps ; Dual-stream: Support; Sub-stream: CIF / QCIF @ 25 fps ; HDD: 4 SATA interfaces , up to 4TB capacity(No HDD Included); eSATA: 1 eSATA interface ; Network interface: 1, RJ45 10M / 100M / 1000M Ethernet interface ; Serial interface: RS-	403€

		232, RS-485 (full-duplex), Keyboard ; Gigabit network interfaces ; USB interface: 3 × USB 2.0 ; Protocols: NTP, SMTP, NFS, UPnP and iSCSI ; Power supply: 100~240VAC, 5A, 50~60Hz ; Consumption: ≤ 40 W ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10% ~ 90%	
28.		32CH Standalone DVR HIKVISION DS-7332HI-SH H.264 video compression ; Video input: 32-ch, BNC (1.0 Vp-p, 75 Ω) ; HDMI / VGA output: 1ch, resolution: 1080P: 1920×1080/60Hz; SXGA: 1280×1024/60Hz; 720P: 1280×720/60Hz; XGA: 1024×768/60Hz ; CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL:704 × 576 ; Audio input: 4-ch, RCA (2.0 Vp-p, 1 kΩ) ; Audio output: 2-ch, RCA (Linear, 600 Ω) ; Alarm in: 16 ; Alarm out: 8 ; 2CIF resolution real-time recording ; Encoding resolution: WD1 / 4CIF / 2CIF / CIF / QCIF ; Frame rate: WD1 / 4CIF: 15 fps, 2CIF / CIF / QCIF: 25 fps ; Dual-stream: Support; Sub-stream: CIF / QCIF @ 25 fps ; HDD: 4 SATA interfaces , up to 4TB capacity(No HDD Included); eSATA: 1 eSATA interface ; Network interface: 1, RJ45 10M / 100M / 1000M Ethernet interface ; Serial interface: RS-232, RS-485 (full-duplex), Keyboard ; Gigabit network interfaces ; USB interface: 3 × USB 2.0 ; Protocols: NTP, SMTP, NFS, UPnP and iSCSI ; Power supply: 100~240VAC, 5A, 50~60Hz ; Consumption: ≤ 40 W ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10% ~ 90%	448€
TURBO HD DVRi			
29.		4CH TURBO HD DVR HIKVISION DS-7104HGHI-SH Support both HD-TVI and analog cameras with adaptive access ; Full channel@720P resolution real-time recording ; HDMI and VGA output at up to 1920×1080P Resolution ; Audio Output: 1-ch RCA(Linear, 1kΩ); Audio Bit Rate: 64kbps ; Support Dual Stream ; Remote connections: 128 ; Interface Type: 1 SATA Interface, Capacity: Up to 4TB capacity for each disk ; Network Interface: 1; 10M / 100M self-adaptive Ethernet interface ; USB Interface: 2 USB 2.0 Interfaces ; Power Supply: 12V DC ; Consumption: ≤ 15W(without hard disks); Working Temperature: -10°C ~+55°C	57€
30.		4CH TURBO HD DVR HIKVISION DS-7204HGHI-SH/A(EU)(B) Video compression: H.264; Analog and HD-TVI video input: 4-ch BNC interface(1.0Vp-p, 75 Ω); Supported camera types: 720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS; Audio compression: G.711u; Audio input / Two-way audio in:4-ch, RCA (2.0 Vp-p, 1 KΩ); Support both HD-TVI and analog cameras with adaptive access; Full channel@720P resolution real-time recording; HDMI and VGA output at up to 1920×1080P resolution; Audio output 1-ch, RCA (Linear, 1KΩ); Network interface: 1; 10M / 100M self-adaptive Ethernet interface; Serial interface 1; standard RS-485 serial interface, half-duplex; USB port: 2 × USB2.0; Power supply 12V DC; Hard Disk type: 4 SATA interfaces for 4 HDDs; 1 eSATA interface, SATA: 1 SATA interface; Capacity Up to 4 TB capacity for each disk (no HDD included); Alarm in/out:4/1; Working temperature: -10 °C ~+55 °C ; Working humidity: 10% ~ 90%; Chassis: 1U chassis.	65.5€
31.		4CH Turbo HD DVR HIKVISION DS-7204HQHI-SH/A(EU)(B) Video compression: H.264; Analog and HD-TVI video input: 4-ch BNC interface(1.0Vp-p, 75 Ω); camera types: 720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS;IP Video input:2ch, up to 1080p resolutions; Audio compression: G.711u; Audio input:4-ch, RCA (2.0 Vp-p, 1 KΩ); Two way audio in: 1 ch RCA(2.0, Vp-p, 1 KΩ); HDMI and VGA output at up to 1920×1080P resolution; Connectable to network cameras at 1080P resolutions; Support both HD-TVI and analog cameras with adaptive access; Audio output: 1ch, RCA; Hard Disk: SATA: 1 SATA interface; Capacity Up to 4 TB capacity for each disk(no HDD included); Alarm in/out : 4/1; Network interface: 1; 10M / 100M self-adaptive Ethernet interface; Serial interface 1; standard RS-485 serial interface, half-duplex; USB port: 2 × USB2.0; Power supply 12V DC; Working temperature: -10 °C ~+55 °C ; Working humidity: 10% ~ 90%; Chassis: 1U chassis.	115€
32.		8CH TURBO HD DVR HIKVISION DS-7208HQHI-SH/A(EU)(B) Video compression: H.264; Analog and HD-TVI video input: 8-ch BNC interface(1.0Vp-p, 75 Ω); camera types: 720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS;IP Video input:2ch, up to 1080p resolutions; Audio compression: G.711u; Audio input:4-ch, RCA (2.0 Vp-p, 1 KΩ); Two way audio in: 1 ch RCA(2.0, Vp-p, 1 KΩ); HDMI and VGA output at up to 1920×1080P resolution; Connectable to network cameras at 1080P resolutions; Support both HD-TVI and analog cameras with adaptive access; Audio output: 1ch, RCA; Hard Disk: SATA: 2 SATA interface; Capacity Up to 4 TB capacity for each disk(no HDD included); Alarm in/out : 8/4; Network interface: 1; 10M / 100M self-adaptive Ethernet interface; Serial interface 1; standard RS-485 serial interface, half-duplex; USB port: 2 × USB2.0; Power supply 12V DC; Working temperature: -10 °C ~+55 °C ; Working humidity: 10% ~ 90%; Chassis: 1U chassis.	182€
33.		16CH TURBO HD DVR HIKVISION DS-7216HGHI-E2/A Video compression: H.264; Analog and HD-TVI video input:16-ch BNC interface(1.0Vp-p, 75 Ω); camera types: 720P25, 720P30, CVBS; IP Video input:2ch, up to 1080p resolutions; Audio compression: G.711u; Audio input:Two way audio in: 1 ch RCA(2.0, Vp-p, 1 KΩ); HDMI and VGA output at up to 1920×1080P resolution; Connectable to network cameras at 1080P resolutions; Support both HD-TVI and analog cameras with adaptive access; Audio output: 1ch, RCA; Hard Disk: SATA: 2 SATA interface; Capacity Up to 6TB capacity for each disk(no HDD included); Alarm in/out : 16/8; Network interface: 1; 10M / 100M self-adaptive Ethernet interface; Serial interface 1; standard RS-485 serial interface, half-duplex; USB port: 2 × USB2.0; Power supply 12V DC; Working temperature: -10 °C ~+55 °C ; Working humidity: 10% ~ 90%; Chassis: 1U chassis.	195€

34.		16CH TURBO HD DVR HIKVISION DS-7216HQHI-SH/A Video compression: H.264; Analog and HD-TVI video input:16-ch BNC interface (1.0Vp-p, 75 Ω); camera types: 720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS;IP Video input:2ch, up to 1080p resolutions; Audio compression: G.711u; Audio input:4-ch, RCA (2.0 Vp-p, 1 KΩ) ;Two way audio in: 1 ch RCA(2.0, Vp-p, 1 KΩ); HDMI and VGA output at up to 1920×1080P resolution; Connectable to network cameras at 1080P resolutions; Support both HD-TVI and analog cameras with adaptive access; Audio output: 1ch, RCA; Hard Disk: SATA: 2 SATA interface; Capacity Up to 4 TB capacity for each disk(no HDD included) ; Alarm in/out : 16/4; Network interface: 1; 10M / 100M self-adaptive Ethernet interface; Serial interface 1; standard RS-485 serial interface, half-duplex; USB port: 2 × USB2.0; Power supply 12V DC; Working temperature: -10 °C ~+55 °C ; Working humidity: 10% ~ 90%; Chassis: 1U chassis.	399€
35.		24CH TURBO HD DVR HIKVISION DS-7324HGHI-SH Video compression: H.264; Analog and HD-TVI video input:24-ch BNC interface (1.0Vp-p, 75 Ω); camera types: 720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS;IP Video input: 8ch, up to 2MP resolutions; Audio compression: G.711u; Audio input:4-ch, RCA (2.0 Vp-p, 1 KΩ) ;Two way audio in: 1 ch RCA(2.0, Vp-p, 1 KΩ); HDMI and VGA outputs at up to 1920×1080P resolutions; Connectable to network cameras at 1080P resolutions; Support both HD-TVI and analog cameras; connectable to the Coaxitron camera/dome with long transmission distance; connectable to network cameras ; Audio output: 1ch, RCA; Hard Disk: SATA: 4 SATA interfaces for 4 HDDs; 1 eSATA interface,Capacity Up to 4 TB capacity for each disk(no HDD included) ; Alarm in/out : 16/4; Network interface: 1; 10M / 100M self-adaptive Ethernet interface; Serial interface: RS-232, RS-485, Keyboard; USB port: 3 × USB2.0; Power supply:100 ~ 240VAC, 47 ~ 63HZ; Working temperature: -10 °C ~+55 °C ; Working humidity: 10% ~ 90%; Chassis: 19-inch rack-mounted 1.5U chassis.	650€
NETWORK VIDEO RECORDERS			
36.		4CH Network Video Recorder HIKVISION DS-7604NI-SE/P 4 Integrated PoE Network Interfaces ; IP Video input: 4-ch ; HDMI/VGA output: 1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768 /60Hz ; Audio input: 1-ch, RCA (2.0 Vp-p, 1kΩ) ; Audio output: 1-ch, RCA (Linear, 1kΩ) ; Up to 5 Megapixels Resolution Recording ; Decoding resolution: 5MP/3MP/ 1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF ; Synchronous playback: 4-ch, 720P / 2-ch, 1080P / 1-ch, 5MP ; HDD Type: 2 SATA interfaces for 2 HDDs, up to 4TB capacity for each disk (No HDD Included) ; Network interface: 1 RJ-45 10 /100 /1000 Mbps self-adaptive ; Ethernet interface: 4 independent 10 /100 Mbps PoE Ethernet interfaces ; Input: 20 Mbps, output: 60 Mbps ; Serial interface: 1 RS-485 half-duplex interface ; USB interface: 2 × USB2.0 ; Power supply: 100~240VAC, 47~63Hz, 3A ; Consumption: > 15 W (without hard disk) ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10%~90%	146€
37.		8CH Network Video Recorder HIKVISION DS-7608NI-SE/P 8 Integrated PoE Network Interfaces ; IP Video input: 8-ch ; HDMI/VGA output: 1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz,1024 × 768 /60Hz ; Audio input: 1-ch, RCA (2.0 Vp-p, 1kΩ) ; Audio output: 1-ch, RCA (Linear, 1kΩ) ; Up to 5 Megapixels Resolution Recording ; Decoding resolution: 5MP/3MP/ 1080p/UXGA/720p/VGA /4CIF/DCIF/2CIF/CIF/QCIF ; Synchronous playback: 8-ch, 4CIF / 4-ch, 720P / 2-ch, 1080P / 1-ch, 5MP ; HDD Type: 2 SATA interfaces for 2 HDDs, up to 4TB capacity for each disk (No HDD Included) ; Network interface: 1 RJ-45 10 /100 /1000 Mbps self-adaptive, Ethernet interface: 8 independent 10 /100 Mbps PoE Ethernet interfaces ; Input: 40 Mbps, output: 80 Mbps ; Serial interface: 1 RS-485 half-duplex interface ; USB interface: 2 × USB2.0 ; Power supply: 100~240VAC, 47~63Hz, 3A ; Consumption: > 15 W (without hard disk) ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10%~90%	169€
38.		16CH Network Video Recorder HIKVISION DS-7616NI-ST IP video input: 16-ch ; CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω), Resolution: 704 × 576; HDMI output: 1-ch, resolution: 1920 × 1080P /60Hz, 1920 × 1080P /50Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720/60Hz, 1024 × 768 /60Hz ; VGA output: 1ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz ; Audio in: 1-ch, BNC (2.0 Vp-p, 1kΩ) (Voice talk input); Audio output: 1-ch, BNC (Linear, 600Ω) ; Alarm in: 4, Alarm out: 2 ; Up to 5 Megapixels resolution recording ; Playback resolution: 5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF ; 16-ch synchronous playback ; Third-party network cameras supported ; HDD Type: 2 SATA interfaces for 2 HDDs, up to 4TB capacity for each disk(No HDD Included) ; Network interface: 1 RJ-45 10 /100 /1000 Mbps self-adaptive ; Ethernet interface: Serial interface: 1 RS-232 interface (for parameters configuration, maintenance, transparent channel); 1 RS-485 interface (reserved); USB interface: 2, USB 2.0 ; Power supply: 12 VDC ; Consumption: ≤ 13 W (without hard disk or DVD-R/W) ; Working temperature: -10 °C ~ +55 °C ; Working humidity: 10%~90%	259€
39.		32CH Network Video Recorder HIKVISION DS-7732NI-ST IP video input: 32-ch ; CVBS output: 1-ch, BNC (1.0 Vp-p, 75 Ω), Resolution:704 × 576; HDMI output: 1-ch, resolution:1920 × 1080P /60Hz, 1920 × 1080P /50Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz,1280 × 720 /60Hz, 1024 × 768 /60Hz ; VGA output: 1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz ; Two-way audio: 1-ch, BNC (2.0 Vp-p, 1kΩ) ; Audio output: 2-ch, BNC (Linear, 600Ω) ; Up to 5 Megapixels resolution recording ; Playback	429€

		resolution: 5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF ; 32-ch synchronous playback ; Alarm in:16, Alarm out:4 ; HDD Type: 4 SATA interfaces for 4 HDDs, up to 4TB capacity for each disk(No HDD Included) ; eSATA: 1 eSATA interface ; Network interface: 1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface ; Serial interface: 1 RS-232 interface (for parameters configuration, maintenance, transparent channel), 1 RS-485 interface (reserved), 1 RS-485 keyboard interface (for special keyboard control) ; USB interface: 3 × USB 2.0 ; Power supply: 100~240VAC, 6.3A, 50~60Hz ; Consumption: ≤ 45 W ; Working temperature: -10 °C ~+55 °C ; Working humidity: 10%~90%	
--	--	--	--

За поголеми количини цените се предмет на договор.

Цените се изразени во евра без пресметан ДДВ 18%.

Камерите не доаѓаат комплет со држач и објектив освен моделите каде што е нагласено дека доаѓаатgratis.

Цените кои се ставени на акција, немаат дополнителен попуст.

ДТУ Визард Системи ДООЕЛ го задржува правото на промена на цените без претходна најава.

